



## **Release Notes OX App Suite v7.2.0**

**(2013-04-11)**

## 1. Packages shipped with this Release

- OX App Suite
  - Version 7.2.0-Rev 4 (built 2013-04-10)

## 2. Additional Information

All changes and bug-fixes listed in this release notes have been done subsequent to 7.0.2-Rev 6 (back-end) and 7.0.1-Rev 5 (front-end).

- Requirements for OX Text - Open-Xchange provides a new technical component "OX Real Time" which is necessary to edit content in a group environment. "Real Time" requires the provided HTTP based connector for the communication between the HTTP server and the backend. This new connector is based on Oracle's Project Grizzly - a NIO and Web framework. Download and configuration instructions are available at <http://oxpedia.org/wiki/index.php?title=AppSuite:Grizzly>
- With v7.2, Open-Xchange provides a new LDAP Contact Storage Integration Bundle. The new solution is available together with the current LDAP bundle. Open-Xchange will then discontinue support for the current bundle with OX App Suite v7.2.1, planned in May 2013. Further configuration information is available at the Open-Xchange Knowledgebase under: <http://oxpedia.org/wiki/index.php?title=ContactStorageLDAP>
- Parallels Operations Automation (POA) is an operations support system (OSS) for service providers who want to differentiate their offerings in order to reduce customer churn and attract new customers. It automates the full lifecycle of hosted services and software — from service management and provisioning to customer self-service and data center management. This integration possibility is now supported with OX App Suite v7.2 and Open-Xchange 6 v6.22.2.
- Open-Xchange discontinues Support for Open-Xchange Server v6.20.7 for all Open-Xchange Server Edition and Hosting Edition. As already announced, Open-Xchange will discontinue maintenance and support for Open-Xchange Advanced Server Edition v6.20.7 on November 30, 2013. Customers with a valid OX Advanced Server Edition maintenance subscription will continue to receive security patches until that date. Customers with valid maintenance can change their system to "Open-Xchange Server Edition for Univention Corporate Server" (OXSE for UCS) at any time free of charge. Further information at <http://knowledgebase.open-xchange.com/download-install/advanced-server-edition/migration-ase-en.html>

### 3. Bugs Fixed with this Release

#### Open-Xchange App Suite

##### Back-End:

- 15313 Mail folders "confirmed-ham" "confirmed-spam" must be subscribed after every login  
Added property  
"com.openexchange.spamhandler.spamassassin.unsubscribeSpamFolders" to  
'spamassassin.properties' to define whether confirmed-spam/confirmed-ham folders  
shall be unsubscribed or not. Default is true.
- 22619 IE 8/9: Security warning pop up is displayed while adding a Facebook account via the  
Wizard/'Add Facebook/Twitter' link  
Fixed in the meantime.
- 22867 Under New Folder Subscribe shows two entries for Facebook  
Drop obsolete subscription source in JSON layer if returned by queried service.
- 23408 SIEVE: multiline subjects in vacation notice corrupt sieve files  
Closed as invalid in agreement with the customer.
- 23480 com.openexchange.context.internal.ContextServiceImpl.getContext does not fall back  
to master, if slaves fails  
Fallback to master was already implemented.
- 23992 Creation and Deletion of folders in Outlook is not reflected or getting delay in front-  
end  
Backend switched completely from former UDP/TCP-based cache invalidation to a  
clustered one utilizing Hazelcast. Cache invalidation now happens in-time.
- 24237 Wrong directory for crawler-files  
Seems to be fixed in the meantime.
- 24581 OX cmdline tools still using \$JAVA\_XTRA\_OPTS instead of newly introduced  
\$JAVA\_OXCMD\_OPTS  
Using only special Java options for CLTs in all scripts starting some CLT.
- 24709 log4j bundle is duplicated in different versions packaged  
Removed duplicate org.apache.log4j bundle.
- 24724 The logging interpretability has become unusable since 6.22 for hosting customers  
Pass stack trace as separate argument to log routine, rather than appending it into log  
message.
- 24853 NPE at InlineImageDataSource  
Already fixed in the meantime.
- 24889 groupware.log: ERROR 'Unknown setting path  
'/modules/mail/contactCollectFolderDeleteDenied.'  
Register preference items regardless of enabled/disabled status.
- 24989 line wrap setting not applied to mails  
Added mapping to config-tree <-> JSlob.

- 25024 'getaccesscombinationnameforuser' does not show updated access combination  
Consider all options when performing hashCode() & equals() methods.
- 25100 6 updates on replication monitor for one "real" update during login  
Use read-only connection to initialize folder cache stuff.
- 25129 Embedded pictures are not shown in unified mail  
Build image location with respect to possibly encoded mail identifier.
- 25141 Files in /tmp/.OX not deleted automatically  
Added central clean-up for possibly uploaded files.
- 25193 external mail account autoconfig uses wrong settings  
More lenient handling when creating mail accounts by auto-config settings. The autoconfig request also returns all information.
- 25221 Missing INTERNALDATE item in FETCH response.  
Ignore FETCH responses that miss requested items.
- 25319 Cannot delete own appointment in shared calendar  
This is expected behavior.
- 25346 My contact data: not all fields get synced to OX  
Support for all contact field by user JSON interface.
- 25348 No helpful error message for customer caused / solvable issues  
Check for possible user-sensitive information and adjust category if any found.
- 25373 OX gets unresponsive and a lot of Unexpected error: sun.nio.cs.MS1252 incompatible with java.lang.String errors in the groupware log  
This is a bug inside IBM Java VM.
- 25407 Webmail user gets a User unfriendly "A severe error occurred" while trying to share his calendar  
Adjusted category accordingly to let proper error message be displayed to user.
- 25421 Infostore: Display Name will not be used after setting / changing within the wizard  
Invoke propagateUserModification if use's display name was changed.
- 25437 Expunging Unified Mail's Trash folder throws error unifiedinbox-2013  
Proper check if specified full name denotes account's trash folder.
- 25438 Possible to add "All users" and "Standard group" as participant of a task in PIM context  
Duplicate of bug #25438.
- 25439 Possible to add "All users" and "Standard group" as participant of an appointment in PIM context  
Check proper user configuration permissions whether resources/groups are accessible in participants dialog.
- 25478 Basic settings - Mail: Insert the original E-Mail text to a reply is not working  
Added entry to 'paths.perfMap' mapping file.
- 25541 "runupdate" fails to execute  
Dropped unresolvable dependency.

- 
- 25673 Executing "showruntimestats" fails with hazelcast stacktrace  
Be aware of possibly removed MBeans during iteration in showruntimestats.
  - 25677 "Upload size exceeded" error message isn't shown in logfile but an "IllegalFormatConversionException" is logged  
Fixed translation issue.
  - 25753 Invalid Content-Type Value for PDF  
Sane Content-Type value.

#### **Front-End:**

- 25134 cannot send mail from external mail account  
Fixed server response parsing.
- 25194 some settings (SSL) for external mail account are not applied  
No longer sending mail\_url and transport\_url because this is derived data.
- 25196 Settings from External Email accounts can not be changed  
Fixed in the meantime.
- 25299 No attachments on iOS  
Enabled uploads for iPad running iOS >= 6.
- 25464 No possibility to add additional mail accounts manually  
Added possibility to manual add the account.
- 25526 Unable to save draft  
Fixed bug in reloading the data.
- 25606 Mailfolder displays about 500 mails only  
Added "Load all" item at the very end of the grid.
- 25632 Inbox folder should appear first  
Fixed order, Unified inbox first (if enabled), then primary inbox.
- 25660 Missing indicator for low priority mails  
Added indicator.
- 25700 email aliases not sorted  
Fixed sorting.
- 25737 HTML mail with pasted text from MS Word not displayed correctly (cut off at upper edge)  
Fixed a line-height issue.

### **OXtender for Business Mobility and USM**

- 24437 Reminder shown without a reminder actually set  
Fixed in the meantime.
- 25182 Serientermine verschwinden auf dem iPhone / iPad  
Always send all exceptions to iPhone.
- 25241 RuntimeException seems to generate several thousand new appointments per day  
Do not read exceptions for deleted series.
- 25322 Several 10000 threads are waiting for one monitor  
Removed synchronization in the SessionStorage when cleaning up old sessions.
- 25603 Encoding of error messages seems to be broken  
USM now also explicitly sets the charset in its response ContentType-header.

## 4. Changes applied

### 4.1. Changes relevant for Administrators

#### 4.1.1. Changes of Configuration Files

##### **Change 1358 - The mDNS bundle is currently only needed if the corresponding cluster discovery service is used**

The default value for "com.openexchange.mdns.enabled" is changed from "true" to "false" in the configuration file ""mdns.properties".

Existing properties should be changed according to the installation status of the cluster-discovery packages: if "cluster-discovery-mdns" is installed, it should be set to "true", otherwise it should be set to the new default value of "false".

##### **Change 1359 - Added file 'preview.properties' for preview-specific config options**

Added file 'preview.properties' for preview-specific config options.

By now that file offers two properties to specify global context-wise quota for caching of preview documents/images.

Specify the total quota for preview cache for each context

This value is used if no individual context quota is defined.

A value of zero or less means no quota; default is zero

com.openexchange.preview.cache.quota=0

Specify the quota per document for preview cache for each context

This value is used if no individual quota per document is defined.

A value of zero or less means no quota; default is zero

com.openexchange.preview.cache.quotaPerDocument=0

##### **Change 1365 - Added configuration property to disable MySQL master/slave replication monitor**

The following additional property is added to the configuration file configdb.properties. This property allows to disable the replication monitor which is not necessary if we want to use synchronous replication of MySQL.

# The following property allows to disable the replication monitor. This option is only useful if you have a MySQL master and slave setup.

# If the application code releases a connection to the MySQL master, a writing operation on the database is assumed. To be able to monitor

# the replication to the slave, a counter is increased after releasing the connection. Reading this counter from the slave indicates, the

# write operation is not replicated yet and instead of a slave connection a master connection is then used to read data. This prevents data

# reading inconsistencies. Unfortunately will this produce additional IO load on MySQL master and slave.

# This mechanism can be disabled with the following property. This saves IO load but it may cause data inconsistencies. Especially newly

# created objects can disappear in the following refresh requests.

com.openexchange.database.replicationMonitor=true

### **Change 1370 - Added configuration files to specify quotas**

Added files that allow the configuration on a context basis for each module (currently tasks, calendar, contacts, and infostore files).

For global server scope there is 'quota.properties' with options for tasks, calendar, contacts, and infostore files. By default all of them are set to "-1" which means no quota limitation:

```
com.openexchange.quota.calendar=-1
com.openexchange.quota.task=-1
com.openexchange.quota.contact=-1
com.openexchange.quota.infostore=-1
```

Furthermore there is file 'quota.yml' in subdirectory "contextSets" that allow config-cascade-wise specification of quotas per context. Each section has the same options as mentioned above and also defaulted to "-1".

### **Change 1384 - Added configuration file 'halo-linkedin.properties' to disable LinkedIn-sensitive Halo operations for inappropriate API key**

Added configuration file 'halo-linkedin.properties' to disable LinkedIn-sensitive Halo operations for inappropriate API key.

That file contains option "com.openexchange.halo.linkedin.enabledMailCapableKey" which is set to "false" by default.

### **Change 1388 - Added property to 'spamassassin.properties' to define whether confirmed-spam/confirmed-ham folders shall be unsubscribed or not**

Added property "com.openexchange.spamhandler.spamassassin.unsubscribeSpamFolders" to 'spamassassin.properties' to define whether confirmed-spam/confirmed-ham folders shall be unsubscribed or not. Default is true.

### **Change 1389 - Added folder option to let default InfoStore folders be labeled with owning user's display name**

Added folder option to let default InfoStore folders be labeled with owning user's display name

File 'foldercache.properties' now contains option "com.openexchange.folderstorage.database.preferDisplayName". Default is "false".

### **Change 1392 - Added tuning options dedicated for web application**

Introduced "-XX:NewRation=3". Meaning young generation is sized with 1/4 of the value specified via -Xmx option.

Web- and transactional application leverage from thread-local heap, that is enabled by default for e.g. IBM, but not for SUN. Thus that option is enabled via "-XX:+UseTLAB".

Both options are added to 'ox-scriptconf' file.

---

## Change 1408 - Changed Apache configuration, new proxy entries for /realtime

App Suite 7.2 introduces a new realtime/push framework for which a new namespace was added to OX URLs.

Please add new proxy entries to the apache configuration to map the /realtime and /atmosphere paths to the backend.

e.g.:

```
<Proxy /atmosphere>
ProxyPass balancer://oxcluster/atmosphere
</Proxy>
<Proxy /realtime>
ProxyPass balancer://oxcluster/realtime
</Proxy>
```

### 4.1.2. Changes of Database Schemes

#### Change 1360 - Add new table 'preview' for caching of preview documents/images

Add new table 'preview' for caching of preview documents/images.

#### Change 1363 - Added new tables 'capability\_context' and 'capability\_user'

Added new tables 'capability\_context' and 'capability\_user' to store context-sensitive or user-sensitive capabilities through admin.

### 4.1.3. Changes of Behavior

- none -

### 4.1.4. Changes of Packaging

#### Change 1390 - Renamed packages for OX Documents

After removal of the package open-xchange-documents-ui, the entire OX Documents app consists of the package open-xchange-documents-ui-manifest. To align OX Documents with the recommended package naming for other apps, the remaining package is renamed to open-xchange-documents-ui, dropping the -manifest suffix.

To upgrade an existing single-server installation:

- remove open-xchange-documents-ui-manifest
- upgrade open-xchange-documents-ui normally

To upgrade an existing distributed installation:

- remove open-xchange-documents-ui-manifest from the OX cluster
- install open-xchange-documents-ui on the OX cluster
- remove open-xchange-documents-ui from the web server cluster

## Change 1401 - Themes and apps with .less files require post-install scripts

To accelerate the login, compilation of LessCSS files was moved from the login process in the browser to the installation process on the backend.

Backend packages for themes and any apps which ship .less files require the following changes:

1. Add "skipLess=1" to the build command in \*.spec and in debian/rules:

```
sh /opt/open-xchange-appsuite-dev/bin/build-appsuite app skipLess=1
```

2. Add %post and %postun sections to \*.spec:

```
%post
if [ "$1" = 1 ]; then
UPDATE=/opt/open-xchange/appsuite/share/update-themes.sh
[ -x $UPDATE ] && $UPDATE
fi
```

```
%postun
UPDATE=/opt/open-xchange/appsuite/share/update-themes.sh
[ -x $UPDATE ] && $UPDATE
```

For multiple binary packages, the %post and %postun sections should apply only to backend packages which contain .less files.

3. Add debian/postinst and debian/postrm containing the same content:

```
#!/bin/sh
UPDATE=/opt/open-xchange/appsuite/share/update-themes.sh
[ -x $UPDATE ] && $UPDATE
```

For multiple binary packages, the postinst and postrm files should apply only to backend packages which contain .less files.

In addition to the above 3 steps, LessCSS files now MUST have the file extension .less to be usable with the 'less' RequireJS plugin (module dependencies of the form 'less!filename.less').

### 4.1.5. Changes of Libraries/Licenses

- none -

### 4.1.6. Changes of Front-End Customizations

All CSS changes and a list of new and changed icons can be found on our wiki page documenting the Theme changes for each version: <http://oxpedia.org/wiki/index.php?title=ThemeChanges>

---

## 4.2. Changes relevant for Developers

### 4.2.1. Changes of the HTTP API

#### Change 1380 - New Calendar Action: `getChangeExceptions`

More efficient retrieval of Change Exceptions of a particular Appointment series.

Parameters:

- session: A session ID previously obtained from the login module.
- id: Object id of the appointment series
- folder: Folder ID of the requested appointments.
- columns: A comma-separated list of columns to return. Each column is specified by a numeric column identifier.

Response:

Response with timestamp: An array with appointment data. Each array element describes one appointment and is itself an array. The elements of each array contain the information specified by the corresponding identifiers in the columns parameter.

### 4.2.2. Changes of the RMI API

#### Change 1366 - Added methods to `add/remove capabilities for a single context or user`

Added methods to `add/remove capabilities for a single context or user`. (see PT 45317545 "Admin can manage minimal app life cycle")

Class `"com.openexchange.admin.rmi.OXUserInterface"` is enhanced by method:  
`changeCapabilities(Context, User, Set<String>, Set<String>, Credentials)`

Class `"com.openexchange.admin.rmi.OXContextInterface"` is enhanced by method:  
`changeCapabilities(Context, Set<String>, Set<String>, Credentials)`

#### Change 1385 - Added methods to `look-up & delete a publication by an URL`

Added methods to `look-up & delete a publication by an URL`.

Introduced new RMI interface `'com.openexchange.admin.rmi.OXPublicationInterface'` whose associated implementation is published via RMI naming service.

### 4.2.3. Changes of the SOAP API

#### Change 1368 - Added methods to add/remove capabilities for a single context or user

Added methods to add/remove capabilities for a single context or user.

Both SOAP WSDLs "http://<ox-host>/servlet/axis2/services/OXContextService?wsdl" and "http://<ox-host>/servlet/axis2/services/OXUserService?wsdl" are enhanced by "changeCapabilities" method.

Sample SOAP request to add a capability for a certain user:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:soap="http://soap.admin.openexchange.com"
xmlns:xsd="http://dataobjects.soap.admin.openexchange.com/xsd"
xmlns:xsd1="http://dataobjects.rmi.admin.openexchange.com/xsd">
<soapenv:Header/>
<soapenv:Body>
<soap:changeCapabilities>
<!--Optional:-->
<soap:ctx>
<!--Optional:-->
<xsd:id>#context-id#</xsd:id>
</soap:ctx>
<!--Optional:-->
<soap:user>
<!--Optional:-->
<xsd:id>#user-id#</xsd:id>
</soap:user>
<!--Optional:-->
<soap:capsToAdd>myCapability</soap:capsToAdd>
<!--Optional:-->
<soap:capsToRemove></soap:capsToRemove>
<!--Optional:-->
<soap:auth>
<!--Optional:-->
<xsd1:login>#admin#</xsd1:login>
<!--Optional:-->
<xsd1:password>#password#</xsd1:password>
</soap:auth>
</soap:changeCapabilities>
</soapenv:Body>
</soapenv:Envelope>
```

## Change 1373 - Added methods to set a module's quota for a single context

Added methods to set a module's quota for a single context.

SOAP WSDLs "http://<ox-host>/servlet/axis2/services/OXContextService?wsdl" and "http://<ox-host>/servlet/axis2/services/OXUserService?wsdl" is enhanced by "changeQuota" method.

Sample SOAP request to add a capability for a certain context:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:soap="http://soap.admin.openexchange.com"
xmlns:xsd="http://dataobjects.soap.admin.openexchange.com/xsd"
xmlns:xsd1="http://dataobjects.rmi.admin.openexchange.com/xsd">
<soapenv:Header/>
<soapenv:Body>
<soap:changeQuota>
<!--Optional:-->
<soap:ctx>
<!--Optional:-->
<xsd:id>#context-id#</xsd:id>
</soap:ctx>
<!--Optional:-->
<soap:module>calendar</soap:module>
<!--Optional:-->
<soap:quotaValue>10000000</soap:quotaValue>
<!--Optional:-->
<soap:auth>
<!--Optional:-->
<xsd1:login>#admin#</xsd1:login>
<!--Optional:-->
<xsd1:password>#password#</xsd1:password>
</soap:auth>
</soap:changeQuota>
</soapenv:Body>
</soapenv:Envelope>
```

## Change 1386 - Added SOAP methods to look-up & delete a publication by an URL

Added SOAP methods to look-up & delete a publication by an URL:

http://<host>/servlet/axis2/services/OXPublicationService?wsdl

Providing appropriate SOAP methods:

deletePublication

getPublication

#### 4.2.4. Changes of the CLT API

##### **Change 1344 - Extension of logincounter CLT for more detailed output and elimination of duplicate login counts**

Now more complex regular expressions (according to <http://dev.mysql.com/doc/refman/5.5/en/regexp.html>) are possible to filter the results by specific clients. The login counts are printed along with their according client identifier.

Example output:

```
Number of logins between
Sun Jan 01 00:00:00 CET 2012
and
Tue Feb 26 00:00:00 CET 2013
for expression
'com.*.dhtml|CALDAV'
with total logins aggregated by users
```

```
client:com.openexchange.ox6.gui.dhtml: 10
client:com.openexchange.ox.gui.dhtml: 139
client:CALDAV: 11
Total: 160
```

Additionally a new parameter "-a, --aggregate" has been introduced. If used, the total login count is aggregated by users to eliminate multiple counts of the same user caused by multiple clients.

##### **Change 1367 - Added methods to add/remove capabilities for a single context or user**

Both CLIs 'changeuser' and 'changecontext' are enhanced by two options to specify what capabilities to add or remove:

```
--capabilities-to-add <capabilities-to-add> The capabilities to add as a comma-separated string
--capabilities-to-remove <capabilities-to-remove> The capabilities to remove as a comma-separated string
```

##### **Change 1374 - Added method to set a module's quota for a single context**

Added method to set a module's quota for a single context.

The CLIs 'changecontext' is enhanced by two options to specify the module and the quota value:

```
--quota-module <quota-module> The identifier of the module to which to apply the quota value
--quota-value <quota-value> The quota value; zero is unlimited
```

---

## Change 1387 - Added CLIs to look-up & delete a publication by an URL

Added CLIs to look-up & delete a publication by an URL

Introduced CLIs 'getpublication' and 'deletepublication'. Both CLIs accept an URL string and appropriate credentials

-h, --help Prints a help text  
--environment Show info about commandline environment  
--nonl Remove all newlines (\n) from output  
-A, --adminuser <adminuser> ? master Admin user name  
-P, --adminpass <adminpass> ? master Admin password  
--publication-url <publication-url> The publication URL

### 4.2.5. Changes of the WebDAV API

- none -

### 4.2.6. Changes of the GUI-API

- none -

## 5. Tests

The OX QA team has verified all bug fixes.

To avoid side effects the packages have gone through automated smoke and regression test on both, the OX Build System and a distributed OX QA server setup.

In addition all bug fixes have been checked for potential side effects or changed behavior. Unless explicitly stated with one of the bug entries above, we do not expect other side effects.

## 6. Fixed Bugs

15313, 22619, 22867, 23408, 23480, 23992, 24237, 24437, 24581, 24709, 24724, 24853, 24889, 24989, 25100, 25129, 25134, 25141, 25182, 25193, 25194, 25196, 25221, 25241, 25299, 25319, 25322, 25346, 25348, 25373, 25407, 25421, 25437, 25438, 25439, 25464, 25478, 25526, 25541, 25603, 25606, 25632, 25660, 25677, 25700, 25737, 25753