



OX App Suite ownCloud Integration Technical Documentation
for
7.10.5

2021-06-22

Copyright notice

©2021 by OX Software GmbH. All rights reserved. Open-Xchange and the Open-Xchange logo are trademarks or registered trademarks of OX Software GmbH. All other company and/or product names may be trademarks or registered trademarks of their owners. Information contained in this document is subject to change without notice.

Contents

1	General Information	2
1.1	Warnings	2
1.2	Delivery Comment	2
1.3	Install Package Repository	2
1.4	Build Dependencies	2
1.5	Notice	3
2	Feature overview about the OX App Suite integration with ownCloud	3
2.1	Motivation	3
2.2	Supported Use Cases	3
3	File Picker UI Plugin for ownCloud	3
3.1	Overview	3
3.1.1	Files App	4
3.2	Installation	4
3.3	Configuration	4
4	File Picker Middleware Plugin for ownCloud	5
4.1	Installation and Configuration	5
5	Session based ownCloud File Storage	5
5.1	Installation and Configuration	5
6	Shipped Packages and Version	6
6.1	Package open-xchange-appsuite-owncloud-filepicker	6
6.1.1	Installation	6
6.1.2	Configuration	6
6.2	Package open-xchange-owncloud-filepicker	6
6.2.1	Installation	6
6.3	Package open-xchange-owncloud-oauth-session	6
6.3.1	Installation	7
6.3.2	Configuration	7
A	Configuration Files	7

1 General Information

1.1 Warnings

Warning

This preview delivery is not for productive usage and not affected by service-level agreements.

Warning

Images included in following pages have been attached as a generic visual reference for the theme and should not be considered as the final aspect when installed on production environment. Actual aspect will change based on components/plugins enabled and their configuration.

Warning

It is mandatory to restart the **open-xchange** service on all middleware nodes after performing the update.

Warning

When updating only custom packages, it may be necessary to invalidate the browser cache to make the changes visible. An invalidation of the cache will be done automatically when updating OX core UI packages at the same time, but not if you are updating only custom UI plug-ins. In the latter case, please call the following command on all Apache nodes with the same value for <timestamp>

```
/opt/open-xchange/sbin/touch-appsuite --timestamp=<timestamp>
```

Warning

UI packages with themes need to generate CSS after installation. This will be done automatically when the service is restarted but if you wish to not perform a service restart, you must call the following command on each node:

```
/opt/open-xchange/appsuite/share/update-themes.sh
```

Warning

Custom configuration or template files are potentially not updated automatically. After the update, please always check for files with a **.dpgk-new** or **.rpmnew** suffix and merge the changes manually. Configuration file changes are listed in their own respective section below but don't include changes to template files. For details about all the configuration files and templates shipped as part of this delivery, please read the relevant section of each package.

1.2 Delivery Comment

This delivery was requested with following comment:

```
OwnCloud Integration 7.10.5 Feature Delivery
```

1.3 Install Package Repository

This delivery is part of a restricted preview software repository:

<https://software.open-xchange.com/components/owncloud-integration/preview/7.10.5/DebianBuster>
<https://software.open-xchange.com/components/owncloud-integration/preview/7.10.5/DebianStretch>
<https://software.open-xchange.com/components/owncloud-integration/preview/7.10.5/RHEL7>

1.4 Build Dependencies

This delivery was build with following dependencies:

```
AppSuite:node-10,frontend-7.10.5-rev13,backend-7.10.5-rev14
```

1.5 Notice

Info

Some configurations can be changed without restarting the service, please call following command for getting a list of supported settings.

```
/opt/open-xchange/sbin/listreloadables
```

Please use following command to enable capable and changed configurations on a running system.

```
/opt/open-xchange/sbin/reloadconfiguration
```

2 Feature overview about the OX App Suite integration with ownCloud

2.1 Motivation

ownCloud customers who need a powerful groupware solution can now share files even more easily with OX App Suite. OX App Suite customers who do not want to miss out on the familiar features in ownCloud now have the option to work with both products.

2.2 Supported Use Cases

OX App Suite now integrates with ownCloud and allows the following use cases:

- ownCloud "Dateien" can be launched in a new browser tab from the OX App Suite App Launcher. The user is automatically logged in to ownCloud.
- Email attachments can be easily selected and attached from ownCloud via a filepicker.
- Files from ownCloud can also be inserted into an email as sharing link. The sharing link has the default settings for the expiration date and no password. The link settings can be maintained in ownCloud.
- The filepicker allows to navigate the ownCloud folder tree. Clicking a folder shows the folder content. The breadcrumb allows to navigate back in the folder tree.
- Checkboxes in the filepicker allow to select a file or folder. Also multiple selection is supported to insert more than one link in the email. Inserting links to folders is also possible.
- Files attached to an email in OX App Suite can be saved in ownCloud. The filepicker allows to select the folder in the ownCloud foldertree where the uploaded attachments are stored.

3 File Picker UI Plugin for ownCloud

Package(s)	open-xchange-appsuite-owncloud-filepicker, open-xchange-appsuite-owncloud-filepicker-static
Required capabilities	com.openexchange.capability.filestorage_owncloud_oauth
Available since	7.10.5

3.1 Overview

This is the UI part of the integration of the [ownCloud file picker](#) into OX App Suite.




Figure 1: File Picker Dialog

3.1.1 Files App

To use the ownCloud Files app instead of the native Drive app in OX App Suite, users should to be provisioned without the `infostore` permission. The integration will add the Files app to the app launcher menu. When clicked, the ownCloud Files app opens in a separate tab.




Figure 2: Files App

3.2 Installation

The UI plugin is available in the packages `open-xchange-appsuite-owncloud-filepicker` and `open-xchange-appsuite-owncloud-filepicker-static`. As usual with UI packages, in case of dedicated web servers, the latter package is installed on the web servers, and the former on middleware nodes.

3.3 Configuration

For a single-node installation where ownCloud and OX App Suite run on the same domain, the integration should work out of the box. By default, the integration assumes that ownCloud is available

unter `/owncloud/` on the same domain. If that is not the case, the exact URL of ownCloud can be configured in

`/opt/open-xchange/etc/settings/owncloud-filepicker.properties:`

```

1 # Custom URL for the ownCloud server.
2 # Defaults to /owncloud/ on the same domain as OX App Suite.
3 #
4 # io.ox.owncloud//server=https://server.tld/owncloud/
5
6 # Custom URL for the ownCloud Files app.
7 # Defaults to apps/files/ relative to the value of io.ox.owncloud//server.
8 #
9 # io.ox.owncloud//appUrl=https://server.tld/owncloud/apps/files/

```

The first option is mainly used to find the WebDAV API endpoint. In addition, the location of the ownCloud Files app is automatically derived from it by appending `apps/files/`. If this does not work, the exact location can be specified explicitly using the second option.

4 File Picker Middleware Plugin for ownCloud

Bundle Identifier	<code>com.openexchange.owncloud.access.token.provider,</code> <code>com.openexchange.owncloud.filepicker</code>
Package(s)	<code>open-xchange-owncloud-filepicker</code>
Required capabilities	<code>com.openexchange.capability.filestorage_owncloud_oauth</code>
Available since	7.10.5

The session based ownCloud file storage allows to use `access_tokens` bound to the session to use attachments from an internal ownCloud account that is connected via the `open-xchange-owncloud-oauth-session` storage.

4.1 Installation and Configuration

The plugin is available through the package `open-xchange-owncloud-oauth-session`. After installation, the filepicker still needs to be enabled explicitly via following capability to `true`:

```
com.openexchange.capability.filestorage_owncloud_oauth
```

5 Session based ownCloud File Storage

Bundle Identifier	<code>com.openexchange.file.storage.owncloud.oauth</code>
Package(s)	<code>open-xchange-owncloud-oauth-session</code>
Required capabilities	<code>com.openexchange.capability.filestorage_owncloud_oauth</code>
Available since	7.10.5

The ownCloud file picker allows to use `access_tokens` bound to the session to create owncloud accounts on the fly.

5.1 Installation and Configuration

The plugin is available through the package `open-xchange-owncloud-oauth-session`. After installation, the storage still needs to be enabled explicitly via following capability to `true`:

```
com.openexchange.capability.filestorage_owncloud_oauth
```

The only other property which must be configured is:

com.openexchange.file.storage.owncloud.oauth.webdav.url

6 Shipped Packages and Version

6.1 Package open-xchange-appsuite-owncloud-filepicker

Integration of the ownCloud file-picker dialog into OX App Suite.

Version: 7.10.5-3

Type: OX Frontend Plugin with Themes

Depends on:

```
open-xchange-appsuite
open-xchange-appsuite-manifest (<<7.10.6)
open-xchange-appsuite-manifest (>=7.10.5)
```

6.1.1 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-appsuite-owncloud-filepicker
```

Install on Apache nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-appsuite-owncloud-filepicker-static
```

6.1.2 Configuration

For details, please see appendix [A](#)

/opt/open-xchange/etc/settings/owncloud-filepicker.properties (page [7](#))

6.2 Package open-xchange-owncloud-filepicker

Module to interact with owncloud filepicker This package provides an endpoints to interact with owncloud filepicker methods

Version: 7.10.5-3

Type: OX Middleware Plugin

Depends on:

```
open-xchange-core (<<7.10.6)
open-xchange-core (>=7.10.5)
```

Conflicts with:

```
open-xchange-custom-filepicker
```

6.2.1 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-owncloud-filepicker
```

6.3 Package open-xchange-owncloud-oauth-session

This package provides a session based file storage for Owncloud

Version: 7.10.5-3

Type: OX Middleware Plugin

Depends on:

```
open-xchange-core (<<7.10.6)
open-xchange-core (>=7.10.5)
```



```
open-xchange-file-storage-webdav (<<7.10.6)
open-xchange-file-storage-webdav (>=7.10.5)
```

Conflicts with:

```
open-xchange-plugins-owncloud-oauth-session
```

6.3.1 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-owncloud-oauth-session
```

6.3.2 Configuration

For details, please see appendix [A](#)

`/opt/open-xchange/etc/owncloud_oauth.properties` (page [7](#))

A Configuration Files

File 1 `/opt/open-xchange/etc/settings/owncloud-filepicker.properties`

```
1 # Custom URL for the ownCloud server.
2 # Defaults to /owncloud/ on the same domain as OX App Suite.
3 #
4 # io.ox.owncloud//server=https://server.tld/owncloud/
5
6 # Custom URL for the ownCloud Files app.
7 # Defaults to apps/files/ relative to the value of io.ox.owncloud//server.
8 #
9 # io.ox.owncloud//appUrl=https://server.tld/owncloud/apps/files/
```

File 2 `/opt/open-xchange/etc/owncloud_oauth.properties`

```
1 # The webdav endpoint for automatic account creation
2 # Should be in the format https://host/owncloud/remote.php/webdav
3 # Default: <empty>
4 com.openexchange.file.storage.owncloud.oauth.webdav.url=
5
6 # The folder name shown in the OX Infostore
7 # Default: ownCloud
8 com.openexchange.file.storage.owncloud.oauth.displayName=ownCloud
9
10 # The capability to enable the automatic handling of ownCloud session based accounts
11 # Default: not_set
12 com.openexchange.capability.filestorage_owncloud_oauth=
13
14 # The capability filestorage_owncloud must also be enabled
15 # Default: not_set
16 com.openexchange.capability.filestorage_owncloud=
```