



OX Cloud Plugins
Release Notes for Release 1.6.9
2019-08-12

Copyright notice

©2019 by OX Software GmbH. All rights reserved. Open-Xchange and the Open-Xchange logo are trademarks or registered trademarks of OX Software GmbH. All other company and/or product names may be trademarks or registered trademarks of their owners. Information contained in this document is subject to change without notice.

Contents

1	General Information	3
1.1	Warnings	3
1.2	Delivery Comment	3
1.3	Install Package Repository	3
1.4	Build Dependencies	4
1.5	Notice	4
2	Shipped Product and Version	4
2.1	Package open-xchange-cloudplugins	4
2.1.1	General Functionality	4
2.1.2	Admin Plugins	5
2.1.2.1	SOAP API	5
2.1.2.2	Admin REST API	5
2.1.3	Authentication Plugin	5
2.1.4	Masterauth Servlet	5
2.1.5	Cassandra	6
2.1.6	Dovecot	6
2.1.7	Mailmapping	6
2.1.8	LDAP Management	7
2.1.8.1	LDAP structure	7
2.1.9	Nginx Servlet	7
2.1.10	Cloud Report	7
2.1.10.1	Requirements	7
2.1.10.2	Report Types	8
2.1.10.3	Usage	8
2.1.10.4	Data Format and Storage	9
2.1.10.5	TKG112 Data Description	10
2.1.10.6	Metrics Data Description	10
2.1.11	Unified Quota	12
2.1.12	Passwordchange	12
2.1.13	Installation	12
2.1.14	Configuration	12
2.2	Package open-xchange-cloudplugins-blackwhitelist-ldap	13
2.2.1	Installation	13
2.2.2	Configuration	13
2.3	Package open-xchange-cloudplugins-mailfilter	13
2.3.1	General Functionality	13
2.3.2	Installation	13
2.3.3	Configuration	14
2.4	Package open-xchange-cloudplugins-saml	14
2.4.1	Installation	14
2.4.2	Configuration	14
2.5	Package open-xchange-externalcontent-ui	14
2.5.1	Installation	14
2.5.2	Configuration	14
2.6	Package open-xchange-oxaas-alias	15
2.6.1	General Functionality	15
2.6.2	Installation	15
2.6.3	Configuration	15
2.7	Package open-xchange-oxaas-mail-notify-ws	15
2.7.1	General Functionality	15
2.7.2	REST API	16
2.7.3	Installation	16
2.7.4	Configuration	16
2.7.5	Templates	16
2.8	Package open-xchange-oxaas-mail-unread-ws	17

2.8.1	General Functionality	17
2.8.2	Installation	17
2.8.3	Configuration	17
2.9	Package open-xchange-oxaas-mail-ws	17
2.9.1	General Functionality	18
2.9.2	Installation	18
2.9.3	Configuration	18
3	Bugs fixed with this Release	18
4	Changes relevant for Operators	19
4.1	Changes of Configuration Files	19
4.2	Changes of Behavior	19
5	Tests	20
5.1	Test Report	20
6	Fixed Bugs	21
A	Configuration Files	22

1 General Information

1.1 Warnings

Warning

It is mandatory to restart the **open-xchange** service on all middleware nodes after performing the update.

Warning

When updating only custom packages, it may be necessary to invalidate the browser cache to make the changes visible. An invalidation of the cache will be done automatically when updating OX core UI packages at the same time, but not if you are updating only custom UI plug-ins. In the latter case, please call the following command on all Apache nodes with the same value for <timestamp> :

```
/opt/open-xchange/sbin/touch-appsuite --timestamp=<timestamp>
```

Warning

Custom configuration or template files are potentially not updated automatically. After the update, please always check for files with a **.dpkg-new** or **.rpmnew** suffix and merge the changes manually. Configuration file changes are listed in their own respective section below but don't include changes to template files. For details about all the configuration files and templates shipped as part of this delivery, please read the relevant section of each package.

Warning

Since Cloud Plugins 1.6.0, the Cassandra functionality has been moved to OX Middleware. This requires manual changes of configuration files because the following settings needs to be changed accordingly:

/opt/open-xchange/etc/cloudplugins-cassandra.properties:

```
com.openexchange.cloudplugins.cassandraHost (1)
com.openexchange.cloudplugins.cassandraPort (2)
```

to */opt/open-xchange/etc/cassandra.properties:*

```
com.openexchange.nosql.cassandra.clusterContactPoints (1)
com.openexchange.nosql.cassandra.port (2)
```

Please see [OX Cassandra documentation](#) for a full set of options.

Warning

Since Cloud Plugins 1.6.4, we removed the packaging epoch mechanism which will prevent an automatic update of open-xchange-oxaas packages from 1.6.3. If your environment contain 1.6.3 open-xchange-oxaas packages, please enforce the update to 1.6.4 or later manually.

1.2 Delivery Comment

This delivery was requested with following comment:

```
First RC of 1.6.9
```

1.3 Install Package Repository

This delivery is part of a public software repository:

<https://software.open-xchange.com/components/cloud-plugins/stable/1.6.9/DebianJessie>

<https://software.open-xchange.com/components/cloud-plugins/stable/1.6.9/RHEL6>

<https://software.open-xchange.com/components/cloud-plugins/stable/1.6.9/RHEL7>

Licensed customers should also configure a restricted software updates repositories by using their credentials:

<https://software.open-xchange.com/components/cloud-plugins/updates/1.6.9/DebianJessie>
<https://software.open-xchange.com/components/cloud-plugins/updates/1.6.9/RHEL6>
<https://software.open-xchange.com/components/cloud-plugins/updates/1.6.9/RHEL7>

1.4 Build Dependencies

This delivery was build and tested with following dependencies:

```
plugins-1.3.7-rev2,frontend-7.8.4-rev53
```

1.5 Notice



Info

Some configurations can be changed without restarting the service, please call following command for getting a list of supported settings.

```
/opt/open-xchange/sbin/listreloadables
```

Please use following command to enable capable and changed configurations on a running system.

```
/opt/open-xchange/sbin/reloadconfiguration
```

2 Shipped Product and Version

2.1 Package open-xchange-cloudplugins

The Open-Xchange cloud plugin bundles

Version: 1.6.9-1

Type: OX Middleware Plugin

Depends on:

```
open-xchange-admin-reseller (>=7.8.4)
open-xchange-admin-soap-reseller (>=7.8.4)
open-xchange-cassandra (>=7.8.4)
open-xchange-rest (>=7.8.4)
```

Conflicts with:

```
open-xchange-authentication
open-xchange-authentication-database
open-xchange-authentication-imap
open-xchange-authentication-ldap
```

2.1.1 General Functionality

The package open-xchange-cloudplugins contains a set of bundles to manage an integrated platform consisting of OX App Suite components and dovecot. It uses some additional software components in order to do that.

- openldap to store information for mail routing used by dovecot and postfix and to act as authentication source
- postfix as mail server

- nginx to act as a proxy for http, imap, pop3 and smtp
- cassandra to store data that often changes like last login attempts, etc.

The package itself contains some OSGi bundles explained in the following sections and the file `cloudplugins.properties` contain configurations shared among each other.

2.1.2 Admin Plugins

Those plugins extend the OX provisioning capabilities. They maintain the data required into the openldap server to do mail routing and authentication using the [2.1.8 LDAP Management](#) functionality. Whenever a context or user is created, deleted or changed, the corresponding data in the ldap server is also updated.

```
com.openexchange.admin.cloudplugins
com.openexchange.admin.cloudplugins.console
```

2.1.2.1 SOAP API

Also in these bundles, there's another SOAP API providing cloud-plugins specific methods. Please see for further details the [OXaaS SOAP API Documentation](#).

2.1.2.2 Admin REST API

Starting with release 1.6.3, there's now also a REST API, check <https://documentation.open-xchange.com> for a link.

Info

Note that in order for this API to be accessible, you need to add an entry like `ProxyPass /oxaas balancer://oxcluster/oxaas` to your `proxy_http.conf`.

2.1.3 Authentication Plugin

This plugin authenticates against the ldap server. To determine the user it needs to know the brand the user is belonging to. This is done using a configurable HTTP host header. This host header is added by the nginx proxy which sits in front of the ox middleware. Please see corresponding file `cloudplugins-authentication.properties` for configuration details.

```
com.openexchange.authentication.cloudplugins
```

2.1.4 Masterauth Servlet

This servlet allows to create an ox http session on behalf of a configurable master login and password without knowing the individual users login and password.

```
com.openexchange.cloudplugins.api.masterauth
```

This servlet provides the following API call which returns a valid OX session.

```
GET /api/oxaas/masterauth/brand/<brand>/context/<contextid>/user/<userid>
```

The following entry must be added to the apache proxy configuration:

```
ProxyPass /api/oxaas balancer://oxcluster/api/oxaas
```

The request has to provide a `X-AUTHENTICATION` header containing the value of

```
Base64( HMAC-SHA1( brand-auth-Key, UTF-8-Encoding-Of( StringToSign ) ) );
```

```
StringToSign = brand " " +
contextid + " " +
userid;
```

brand-auth-key is the value of the ldap nginxAuthKey Attribute of the brand entry. In addition to that, the requestor has to implement HTTP Basic auth using a configured master login and password. How to generate the X-AUTHENTICATION header with perl:

```
perl -MMIME::Base64 -MDigest::HMAC_SHA1=hmac_sha1
-e 'print encode_base64(hmac_sha1("example.com 24 3","secret"))." ;"'
```

How to test with wget:

```
wget -dv --user=admin --password=secret
--header='X-AUTHENTICATION: 6cmrSTcWCcyOV7mzkSgHDbk8RI='
http://example.com/api/oxaas/masterauth/brand/example.com/context/24/user/3 -O -
```

The `cloudplugins-master-auth-servlet.properties` configuration file belongs to this servlet.

2.1.5 Cassandra

This bundle utilizes the cassandra bundle from the ox middleware to read and write data from/to a cassandra cluster.

```
com.openexchange.cloudplugins.cassandra
```

As of now, the following data structures have to be created in order to use this bundle.

```
1 $ cqlsh
2
3 create keyspace ox WITH REPLICATION = { 'class' : 'SimpleStrategy', 'replication_factor' :
4     1 };
5 use ox;
6 CREATE TYPE login_info ( login_time timestamp, ip_address text);
7 CREATE TABLE logins (ox_id text PRIMARY KEY, brand text, logins map<text, frozen<
8     login_info>> );
9 CREATE TABLE failure_logins (ox_id text PRIMARY KEY, brand text, login_errors map<text,
10    int>);
11 CREATE TABLE alias_log ( alias text PRIMARY KEY, brand text, creation_date timestamp,
12    deletion_date timestamp, ox_id text );
13 CREATE TABLE quota_usage ( ox_id text, type text, usage bigint, count bigint, primary key
14    ((ox_id), type));
```



The complete bundle can be turned off and some functionality must be configured per brand. See corresponding configuration file `cloudplugins-cassandra.properties`.

2.1.6 Dovecot

This is an interface to the doveadm REST API of dovecot. Right now it only implements querying the mail quota usage of users.

```
com.openexchange.cloudplugins.dovecot
```

The `doveadm-config.properties` configuration file belongs to this interface.

2.1.7 Mailmapping

The mail mapping is required to integrate with OX Guard. It resolves an email address into a context and userid.


```
com.openexchange.cloudplugins.mailmapping
```

2.1.8 LDAP Management

This provides methods to maintain data in the LDAP server.

```
com.openexchange.cloudplugins.management
```

2.1.8.1 LDAP structure

The ldap schema used with these bundles can be found in the `ldap` folder within this git repository. The ldap tree consists of three main branches:

- 1. The brand tree contains the brand accounts with all users belonging to each brand below.
- 2. The configuration tree containing configuration entries like mailstores, mailservers, etc.
- 3. The context tree containing all contexts of all brands in the entire system.

A brand is the same as a subadmin in the ox reseller bundle. This reseller bundle is a requirement to run the cloud-plugins environment. Due to the fact that all users within a brand are in the tree below a brand, user logins must not be unique within contexts as it is usually in an open-xchange environment, they must be unique within each brand. For details about the reseller bundle please see the [Reseller Bundle Documentation](#).

2.1.9 Nginx Servlet

This provides a servlet used by Nginx to authenticate external IMAP, POP and SMTP users against the ox cloud-plugins scheme.

```
com.openexchange.cloudplugins.nginx.auth.servlet
```

Where users directly using OX webmail are authenticated using the [2.1.3 Authentication Plugin](#), external IMAP, POP and SMTP logins must also be mapped from the internal `uid@contextid` representation to a login string the corresponding brand prefers. This might be an email address, a phone number, or whatever else. Nginx acts as a IMAP, POP and SMTP proxy in front of dovecot and uses the nginx auth servlet as an authentication and transformation source to provide dovecot with the internal login id after it successfully authenticated the user. See corresponding configuration file `nginx-auth-servlet.properties`.

2.1.10 Cloud Report

This is a central tool to get service usage informations on user level. Therefore the administrator has different options to generate this report, which are explained later. The report procession is designed to be highly efficient in regard of memory and cpu usage. If not configured otherwise, the used resources should never interfere with the processes of the operating system. While in procession, parts of the report are stored on hdd, merged into the resulting report and deleted, when the report is done. The report is processing each relevant schema in its own thread and all schemas in parallel for maximum speed. See corresponding configuration file `cloudplugins_report.properties`.

```
com.openexchange.cloudplugins.report
```

2.1.10.1 Requirements

The report loads data from OX-DB as well as cassandra and LDAP storage. If no cassandra or OX-DB connection can be established, the report will not start. Without a valid LDAP connection, errors will be logged inside the report.

2.1.10.2 Report Types

Currently, there are two report types.

- Metrics - The original cloud-plugins report which provides user usage information in JSON.
- TKG112 - Provides user alias information in CSV.

These report types are described further below.

2.1.10.3 Usage

In general, there can be only one report processed at a time. A second report will be denied and the ID of the current report will be displayed. This report can be aborted with the corresponding option and all stored data will be deleted. During procession, the current status can be requested and the user will be provided with all finished contexts compared to totals.

Warning

The processed contexts will only be updated when the schema is completely processed to evade potential bottlenecks because of Object locks.

```

1 Usage: createreport
2 -h,--help                Prints a help text
3   --environment          Show info about commandline environment
4   --nonl                 Remove all newlines (\n) from output
5   --responsetimeout <responsetimeout>
                           response timeout in seconds for reading
                           response from the backend (default 0s; infinite)
6 -A,--adminuser <adminuser> * master admin user name
7 -P,--adminpass <adminpass> * master admin password
8 -s,--timeframe-start <timeframe-start>
                           Set the starting date of the desired
                           timeframe in which the user logins are considered, format: dd.mm.yyyy.
9 -e,--timeframe-end <timeframe-end>
                           Set the ending date of the desired
                           timeframe in which the user logins are considered, in format: dd.mm.yyyy.
10 -a,--ignore-admin
                           Ignore admins and dont show users of
                           that category in the report.
11 -d,--show-drive-metrics  Add drive metrics for every user.
12 -m,--show-mail-metrics  Add mail metrics for every user.
13 -b,--single-brand <single-brand>
                           Create a report for the selected brand
                           only. Identified by the brand admins sid.
14 -t,--terminate-report
                           Terminates the currently processed
                           report uuid.
15 -p,--pending-reports    Get the status of the pending report.
16
17 Entries marked with an asterisk (*) are mandatory.
18 Entries marked with an question mark (?) are mandatory depending on your
19 configuration.
20 Entries marked with a pipe (|) are mandatory for one another which means that
21 at least one of them must be set.

```



```

1 Usage: createtkg112report
2 -h,--help                Prints a help text
3   --environment          Show info about commandline environment
4   --nonl                 Remove all newlines (\n) from output
5   --responsetimeout <responsetimeout>
                           response timeout in seconds for reading
                           response from the backend (default 0s; infinite)
6 -A,--adminuser <adminuser> * master admin user name
7 -P,--adminpass <adminpass> * master admin password
8 -b,--single-brand <single-brand>
                           * Brand to create report for. Identified
                           by the brand admins sid.
9 -t,--terminate-report
                           Terminates the currently processed
                           report uuid.
10 -p,--pending-reports    Get the status of the pending report.
11
12 Entries marked with an asterisk (*) are mandatory.
13 Entries marked with an question mark (?) are mandatory depending on your
14 configuration.

```

15 Entries marked with a pipe (|) are mandatory for one another which means that
 16 at least one of them must be set.



2.1.10.4 Data Format and Storage

The Metrics Report data is stored in JSON format and looks like the example below.

```

1  {
2    "uuid":"28b3573af6734877a448ab614698d115",
3    "reportType":"OXaaS-report",
4    "timestamps":{
5      "start":1498477236283,
6      "stop":1498477276490
7    },
8    "version":{
9      "buildDate":"01.01.2017",
10     "version":"7.8.3"
11   },
12   "configs":{
13     "options":{
14       "show-drive-metrics":false,
15       "timeframe-start":1466941236283,
16       "show-mail-metrics":false,
17       "single-brand":0,
18       "ignore-admin":true,
19       "timeframe-end":1498477236283
20     }
21   },
22   "errors":{
23     "Exception-ID":"ERROR-ID Categories=ERROR Message='Message' exceptionID=Exception-ID
24     "
25   },
26   "oxaas":{
27     "capabilitySets":{
28       "283724704":"autologin,blacklist,...",...
29     },
30     "brandname":{
31       "totals":{
32         "quota" : 2621440000,
33         "quotaUsage" : 2522466,
34         "mailQuota" : 45365,
35         "mailQuotaUsage" : 0
36       },
37       "1":{
38         "3":{
39           "capabilitySet":"283724704",
40           "drive" : {
41             "mime-types" : {
42               "text/plain" : 5,
43               "application/zip" : 2
44             },
45             "file-count-all-versions" : 7,
46             "quota" : 104857600,
47             "used-quota" : 2511077,
48             "file-size-min" : 5,
49             "file-count-latest-version" : 7,
50             "file-size-avg" : 358725,
51             "file-size-max" : 1255526
52           },
53           "mail" : {
54             "mail-quota" : 2048,
55             "mail-quota-usage" : 0
56           },
57           "imap-login":"301",
58           "login-info":"adam@brandname",
59           "email":"adam@brandname",
60           "user-logins":{
61             "HTTP" : 1497364334092,

```

```

61     "open-xchange-appsuite" : 1497364334090
62     },
63     "unified-quota-enabled":true,
64     "unified-quota-limit":104859648,
65     "unified-quota":2511533
66   }
67 }
68 }
69 }
70 }

```



The TKG112 Report data is stored in CSV format and looks like the example below. It will output an additional file with _info appended that contains configuration information as well as errors.

```

1  Email_nameID, Email_Displayname, Email_Begin, Email_Address, Email_Create, Email_Remove,
   Email_isactive
2  ID1, TestUser1, 2016-12-06 14:11:00 +0000, testuser@brand.com, 2016-12-06 14:11:00 +0000,
   , true
3  ID2, TestUser2, 2016-12-06 14:11:00 +0000, testuser2@brand.com, 2016-12-06 14:11:00 +0000,
   2016-12-06 14:11:00 +0000, false

```



2.1.10.5 TKG112 Data Description

All

- Email_nameID - Varchar (256) - OX "userName"
- Email_Displayname - Varchar (320) - Displayname used when sending emails
- Email_Begin - Date (YYYY-MM-DD hh:mm:ss TIME_ZONE) - Date of the registration in the OX system
- Email_Address - Varchar (256) - email address including the domain name
- Email_Create - Date (YYYY-MM-DD hh:mm:ss TIME_ZONE) - Date when the email address was created
- Email_Remove - Date (YYYY-MM-DD hh:mm:ss TIME_ZONE) - Date when the email address was removed (optional)
- Email_isactive - Boolean true/false - Flag if the email account is active or not. Will be always true when Email_Remove is empty.

2.1.10.6 Metrics Data Description

General

- uuid - The report identifier
- reportType - Type of this report, so far only "OXaaS-report" possible
- timestamps - The start and end time of the report in milliseconds
- version - The builddate and version of the processing server
- errors - Map of all errors occurred during procession. Key is the exception Id and value is further information like message, category and Error-Id

Configs

- show-drive-metrics - true or false
- timeframe-start - The used timeframe start, if not set by the user, one year in the past is used
- show-mail-metrics - true or false
- single-brand - The sid of the brand admin or 0 if not set
- ignore-admin - true or false
- timeframe-end - The used timeframe end, if not set, the starting time of the report is used

OXaaS

- capabilitySets - All capability sets determined by the report. Key is the hashed value of all capabilities in a list
- brandname - The brandname with all userdata for the brand

Per Brand

- totals - Drive and mail quota information for the whole brand, comulated values of all users.
- contexts - All context informations for this brand

Per User

- capabilitySet - The hash value of the capability-set this user has
- drive - All drive data for this user (only present if drive option is true)
- mail - All mail data for this user (only present if mail option is true)
- imap-login - Imap login address
- login-info - Login info, gather from LDAP
- email - users email address
- user-logins - A list of all protocols, the user used to login with the latest timestamp as milliseconds
- unified-quota-enabled - true or false
- unified-quota-limit - This users unified quota limit (only present if unified quota is enabled for this user)
- unified-quota - This users unified quota (only present if unified quota is enabled for this user)

Drive Data

- mime-types - Map of all mimetypes and their amount
- file-count-all-versions - Number of all files and versions for this user
- quota - Quota limit
- used-quota - Used quota
- file-size-min - Smallest file size in this storage
- file-count-latest-version - Number of files, respecting only the latest version
- file-size-avg - Average filesize
- file-size-max - Maximum filesize

Quota Data Sources With unified quota enabled

- drive limit - From LDAP

- drive quota - From Cassandra
- mail limit - From LDAP
- mail quota - From Cassandra

Without Unified Quota

- drive limit - From filestore
- drive quota - From filestore
- mail limit - From LDAP
- mail quota - From Cassandra

2.1.11 Unified Quota

This implements the unified quota feature for cloud-plugins. It requires cassandra to be running and initialized with the `quota_usage` table, see [2.1.5 Cassandra](#) section. All file quota usage is updated into and read from cassandra.

```
com.openexchange.cloudplugins.unifiedquota
```

Please see for information about how to use this bundle the [Unifiedquota Documentaion](#)

2.1.12 Passwordchange

This implements the ox password change callback API in order to be able to change passwords in LDAP.

```
com.openexchange.passwordchange.cloudplugins
```

2.1.13 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-cloudplugins
```

2.1.14 Configuration

For details, please see appendix [A](#)

[/opt/open-xchange/etc/plugin/mailstore-cloudplugins.properties](#) (page [22](#))

[/opt/open-xchange/etc/cloudplugins-authentication.properties](#) (page [22](#))

[/opt/open-xchange/etc/cloudplugins-master-auth-servlet.properties](#) (page [22](#))

[/opt/open-xchange/etc/cloudplugins-cassandra.properties](#) (page [23](#))

[/opt/open-xchange/etc/cloudplugins.properties](#) (page [24](#))

[/opt/open-xchange/etc/doveadm-config.properties](#) (page [24](#))

[/opt/open-xchange/etc/nginx-auth-servlet.properties](#) (page [25](#))

[/opt/open-xchange/etc/cloudquotaservice.properties](#) (page [26](#))

[/opt/open-xchange/etc/cloudquotaservice-cassandra.properties](#) (page [27](#))

[/opt/open-xchange/etc/cloudplugins_report.properties](#) (page [27](#))

2.2 Package open-xchange-cloudplugins-blackwhitelist-ldap

Implementation of blacklist whitelist for cloudplugins within LDAP

Version: 1.6.9-1

Type: OX Middleware Plugin

Depends on:

```
open-xchange-cloudplugins (>=1.6.9)
open-xchange-core (>=7.8.4)
open-xchange-plugins-blackwhitelist (>=1.3.0)
```

2.2.1 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-cloudplugins-blackwhitelist-ldap
```

2.2.2 Configuration

For details, please see appendix [A](#)

/opt/open-xchange/etc/cloudplugins-blackwhitelist-ldap.properties (page [28](#))

2.3 Package open-xchange-cloudplugins-mailfilter

CloudPlugins MailFilter Utilities This package implements a mailfilter interceptor driver framework and provides some useful drivers.

Version: 1.6.9-1

Type: OX Middleware Plugin

Depends on:

```
open-xchange-cloudplugins (>=1.6.9)
open-xchange-core (>=7.8.4)
open-xchange-mailfilter (>=7.8.4)
```

2.3.1 General Functionality

This plugin provides a mailfilter interceptor driver framework and some useful drivers. List of features implemented by this plugin:

- Registers a MailFilterInterceptor
 - Automatically starts a Driver Manager which tracks MailFilterInterceptor Drivers
 - When a user creates/updates/deletes a filter rule, the driver manager will run each driver that is supported for that user in order of their rank.
- Provides MailFilterInterceptor Drivers - configured via their enabled property
 - RedirectStatusDriver - supports any user in any of the configured brands and tells CloudManagementCassandraService the autoforward status and how many redirects exist.
 - RedirectBlacklistDriver - supports Config Cascade. Blocks users from creating only autoforward or all redirect mail filter rules that use a To Address that is blacklisted.

2.3.2 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-cloudplugins-mailfilter
```

2.3.3 Configuration

For details, please see appendix [A](#)
/opt/open-xchange/etc/mailfilter-interceptor-drivers.properties (page [29](#))

2.4 Package open-xchange-cloudplugins-saml

SAML backend for any default Identity Server This package contains an SAML backend for any Identity Server, that fully supports the SAML protocol.

Version: 1.6.9-1

Type: OX Middleware Plugin

Depends on:

```
open-xchange-cloudplugins (>=1.6.9)  
open-xchange-saml-core (>=7.8.4)
```

2.4.1 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-cloudplugins-saml
```

2.4.2 Configuration

For details, please see appendix [A](#)
/opt/open-xchange/etc/cloudplugins-saml.properties (page [30](#))

2.5 Package open-xchange-externalcontent-ui

External content portal plugin

Version: 1.6.9-1

Type: OX Frontend Plugin

Depends on:

```
open-xchange-appsuite-manifest (>=7.8.4)
```

2.5.1 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-externalcontent-ui
```

2.5.2 Configuration

For details, please see appendix [A](#)
/opt/open-xchange/etc/settings/externalcontent.properties (page [30](#))

2.6 Package open-xchange-oxaas-alias

OXaaS alias bundle This package implements OXaaS alias handling.

Version: 1.6.9-1

Type: OX Middleware Plugin

Depends on:

```
open-xchange-admin (>=7.8.4)
open-xchange-core (>=7.8.4)
```

2.6.1 General Functionality

The plugin is available to everyone on the installed system.

List of features implemented by this plugin:

- Alias are provided through internal and external APIs
- add and all requests are backed by a Tarent adapter
- del request is handled internally by using the internal provisioning interfaces
- max concurrent aliases are set by config-cascade aware setting `com.openexchange.oxaas.aliasquota` with default of 15.

2.6.2 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-oxaas-alias
```

2.6.3 Configuration

For details, please see appendix [A](#)

`/opt/open-xchange/etc/oxaas-alias.properties` (page [31](#))

2.7 Package open-xchange-oxaas-mail-notify-ws

OXaaS notification mail servlet bundle

Version: 1.6.9-1

Type: OX Middleware Plugin

Depends on:

```
open-xchange-cloudplugins (>=1.6.9)
open-xchange-core (>=7.8.4)
open-xchange-ldap (>=7.8.4)
open-xchange-rest (>=7.8.4)
open-xchange-smtp (>=7.8.4)
```

2.7.1 General Functionality

The plugin is available to everyone that has correctly setup configuration.

List of features implemented by this plugin:

- Configuration for templates are done on a config-cascade base

- `com.openexchange.oxaas.mail.quota.notify.prefix`
with default value `notify.oxaas.over.quota`
- `com.openexchange.oxaas.mail.welcomemail.notify.prefix`
with default value `notify.oxaas.welcome.mail`
- `com.openexchange.oxaas.mail.removed.sent.spam.notify.prefix`
with default value `notify.oxaas.disable.sent.spam`
- The above prefix is used for the templates where each template must have `${prefix}.${quotavalue}.[html|subject|text].tmpl` files present, in the case of the over quota mails. For the others, it is `${prefix}.[html|subject|text].tmpl`
- Default files are provided for 90% and 100% with the prefix `notify.oxaas.over.quota`.
- `com.openexchange.noreply.address` must be set via config-cascade, otherwise this feature won't work.
- `com.openexchange.oxaas.mail.(quota|welcomemail|removed.sent.spam).ignoreFooterImage` can be set via config-cascade to disable footerImage added as attachment to the mail, or by using `com.openexchange.oxaas.mail.ignoreFooterImage` that applies to all types

2.7.2 REST API

This package implements the OXaaS mail notification generation servlet which will return several mails via a REST API:

```
1 /api/oxaas/notification/mail/quota/{usercontext}/ (JSON body: {"quota_threshold":"..."})
2 /api/oxaas/notification/mail/welcomemail/{usercontext}/
3 /api/oxaas/notification/mail/disable_sent_spam_notification/{usercontext}/
```



2.7.3 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-oxaas-mail-notify-ws
```

2.7.4 Configuration

For details, please see appendix [A](#)

`/opt/open-xchange/etc/oxaas-mail-notification-templates.properties` (page [31](#))

`/opt/open-xchange/etc/oxaas-drive-quota-notification.properties` (page [31](#))

2.7.5 Templates

`/opt/open-xchange/templates/notify.oxaas.over.quota.90.text.tmpl`

`/opt/open-xchange/templates/notify.oxaas.over.quota.90.subject.tmpl`

`/opt/open-xchange/templates/notify.oxaas.over.quota.100.subject.tmpl`

`/opt/open-xchange/templates/notify.oxaas.over.quota.90.html.tmpl`

`/opt/open-xchange/templates/notify.oxaas.over.quota.100.html.tmpl`

`/opt/open-xchange/templates/notify.oxaas.over.quota.100.text.tmpl`

2.8 Package open-xchange-oxaas-mail-unread-ws

OXaaS mail custom mail servlet bundle This package implements OXaaS mail servlet to gather information via rest api.

Version: 1.6.9-1

Type: OX Middleware Plugin

Depends on:

```
open-xchange-cloudplugins (>=1.6.9)
open-xchange-core (>=7.8.4)
open-xchange-imap (>=7.8.4)
```

2.8.1 General Functionality

API to featch the user related unread count for INBOX

List of features implemented by this plugin:

- API is reachable at `http://localhost:8009/preliminary/api/oxaas/mail/unread/<useridenfier>`
- API is secured by `oxaas-mail-unread.properties` where it is possible to add configuration for each brand that should have this feature enabled
- Set `com.openexchange.oxaas.mail.unread.ws.basic.usernames=hosterone`
- Set `com.openexchange.oxaas.mail.unread.ws.basic.hosterone.brand=internalBrandForhosterone`
- Set `com.openexchange.oxaas.mail.unread.ws.basic.hosterone.password=verySecretPassword`

2.8.2 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-oxaas-mail-unread-ws
```

2.8.3 Configuration

For details, please see appendix [A](#)

`/opt/open-xchange/etc/oxaas-mail-unread.properties` (page [32](#))

2.9 Package open-xchange-oxaas-mail-ws

OXaaS mail custom mail servlet bundle This package implements OXaaS mail servlet to gather information via rest api.

Version: 1.6.9-1

Type: OX Middleware Plugin

Depends on:

```
open-xchange-cloudplugins (>=1.6.9)
open-xchange-core (>=7.8.4)
open-xchange-imap (>=7.8.4)
```

2.9.1 General Functionality

This plugin provides a middleware restfull API to retrieve details of customerdata.
List of features implemented by this plugin:

- Main entry point is **/api/oxaas/mail**
- secured by basic auth mapped to customer brand
- **/api/oxaas/mail/{uid}/recentmails** returns latest 5 mails in INBOX
- **/api/oxaas/mail/{uid}/quota** returns current mailbox quota
- **/api/oxaas/mail/{uid}/newmessages** returns the number of new mails since last login
- **/api/oxaas/mail/{uid}** all of the above combined

2.9.2 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-oxaas-mail-ws
```

2.9.3 Configuration

For details, please see appendix [A](#)
`/opt/open-xchange/etc/oxaas-mail.properties` (page [32](#))

Find more information about product versions and releases at http://oxpedia.org/wiki/index.php?title=AppSuite:Versioning_and_Numbering and <http://documentation.open-xchange.com/>.

3 Bugs fixed with this Release

This section provides a summary of bug fixes and changes that have been applied subsequently to shipping Release 1.6.8. Some of the announced bug fixes may have already been fixed at the existing code-base via Patch Releases.

CP-131 User mailstoreDN attribute may never be removed

Status: Done
Resolution: Fixed
Affected Packages: open-xchange-cloudplugins

CP-161 listdomaincatchall does not work

Status: Done
Resolution: Fixed
Labels: 1.6.8 1.8.4 MIJ_ISSUE
Affected Packages: open-xchange-cloudplugins

CP-163 Default authentication driver is unable to handle login by alias

Status: Done
Resolution: Fixed
Affected Packages: open-xchange-cloudplugins

CP-167 Erroneous check for user ID or user name being set in getUser()

Status: Done
Resolution: Fixed

Labels: 1.6.8 1.8.5

Affected Packages: open-xchange-cloudplugins

CP-170 LdapStorage.getUserQuotaForContexts() always fails

Status: Done

Resolution: Fixed

Labels: 1.6.8 1.8.5

Affected Packages: open-xchange-cloudplugins

CP-175 cassandra quota driver: NPE in OXCloudService.getQuotaUsagePerUser in case there's no entry in the db

Status: Done

Resolution: Fixed

Labels: 1.6.8 1.8.4

Affected Packages: open-xchange-cloudplugins

CP-179 deleteuser on a guest user results in an exception

Status: Done

Resolution: Fixed

Affected Packages: open-xchange-cloudplugins

CP-181 CassandraCloudQuotaServiceDriver doesn't take unified quota into account

Status: Done

Resolution: Fixed

Affected Packages: open-xchange-cloudplugins

4 Changes relevant for Operators

4.1 Changes of Configuration Files

Change #1 /opt/open-xchange/etc/cloudquotaservice-cassandra.properties

```
+com.openexchange.cloudplugins.quota.unified.quota=
```

Package: open-xchange-cloudplugins

4.2 Changes of Behavior

Change #CP-162 Unique Mail Addresses per Context

Status: Done

Resolution: Done

Labels: 1.6.9 1.8.5

Affected Packages: open-xchange-cloudplugins

Change #CP-165 Prevent login using an alias that is present more than once in a context

Status: Done

Resolution: Done

Labels: 1.6.9 1.8.5

Change #CP-168 String formatting error masks exception when creating an alias that already exists

Status: Done

Resolution: Fixed

Affected Packages: open-xchange-cloudplugins

Change #CP-171 Enable all tests for cloud-plugins

Status: Done

Resolution: Fixed

Affected Packages: open-xchange-cloudplugins
open-xchange-oxaas-mail-notify-ws**Change #CP-176 cassandra quota driver: No entry in the DB before first login**

Status: Done

Resolution: Fixed

Labels: 1.6.8 1.8.5

Affected Packages: open-xchange-cloudplugins

Change #CP-182 Delete APS2 packages

Status: Done

Resolution: Done

Source Directory: Jenkinsfile

cloud-plugins-packages

com.openexchange.cloudplugins.aps2.upsell

com.openexchange.cloudplugins.aps2.upsell.json

open-xchange-aps2-upsell-ui

open-xchange-cloudplugins-aps2-upsell

5 Tests

Not all defects that got resolved could be reproduced within the lab. Therefore, we advise guided and close monitoring of the reported defect when deploying to a staging or production environment. Defects which have not been fully verified, are marked as such.

To avoid side effects, the shipped packages have gone through automated regression test on both, a Continuous Integration System and a dedicated server set-up for system and integration testing. All changes have been checked for potential side-effects and effect on behavior. Unless explicitly stated within this document, we do not expect any side-effects.

5.1 Test Report

Test T1530019 External Content Portal Widget - Pre-configured case (cloud-plugins-1.6.9-rev1)

Status: Passed

This case covers the "pre-configured" scenario. With a configuration file, forces an immovable portal widget onto the user's Portal application in the first slot, displaying a pre-configured external URL (such as an account page, etc.) NOTE: The external content displayed may encounter a same-origin policy error, wherein the browser will refuse to display the external URL's content in the iframe if the remote server does not allow that behavior.

Test T1530020 Restrict mail access (cloud-plugins-1.6.9-rev1)

Status: Passed

If a user has access-webmail off, this must be written into LDAP

Test T1530021 Record logging of Http protocol with valid credentials (cloud-plugins-1.6.9-rev1)

Status: Passed

[Jira CP-4](#)**Test T1530022 Record logging of Smtplib protocol with valid credentials (cloud-plugins-1.6.9-**

rev1)

Status: Passed

[Jira CP-4](#)**Test T1530023 Record logging of IMAP protocol with valid credentials (cloud-plugins-1.6.9-rev1)**

Status: Passed

[Jira CP-4](#)**Test T1530024 Record the creation time of Email Alias (cloud-plugins-1.6.9-rev1)**

Status: Passed

[Jira CP-14](#)**Test T1530025 Record the quota information in Quota Usage table in Cassandra (cloud-plugins-1.6.9-rev1)**

Status: Passed

Verify the quota logging in database

[Jira MW-442](#)**Test T1530026 User master authentication (cloud-plugins-1.6.9-rev1)**

Status: Passed

[Jira CP-1](#)**Test T1530027 Get user with option attributes (cloud-plugins-1.6.9-rev1)**

Status: Passed

[Link](#)**Test T1530028 Record creation and deletion of AutoForward sieve filter in Cassandra table (cloud-plugins-1.6.9-rev1)**

Status: Passed

[Jira CP-110](#)**Test T1530029 Get User configuration (cloud-plugins-1.6.9-rev1)**

Status: Passed

[Jira CP-93](#)**Test T1530030 Configuration (cloud-plugins-1.6.9-rev1)**

Status: Passed

Test T1530031 Auto forward (cloud-plugins-1.6.9-rev1)

Status: Passed

Test T1530032 Use Nginx Auth with Alias (cloud-plugins-1.6.9-rev1)

Status: Passed

6 Fixed Bugs

[CP-131](#), [CP-161](#), [CP-163](#), [CP-167](#), [CP-170](#), [CP-175](#), [CP-179](#), [CP-181](#),

A Configuration Files

File 1 /opt/open-xchange/etc/plugin/mailstore-cloudplugins.properties

```
1 MAILSTORE_CLOUD_STORAGE=com.openexchange.admin.cloudplugins.storage.mysqlStorage.  
   MailstoreCloudMySQLStorage
```

File 2 /opt/open-xchange/etc/cloudplugins-authentication.properties

```
1 # Regex to validate host HTTP Header value  
2 com.openexchange.authentication.cloudplugins.host.regex= [0-9a-zA-Z.]*  
3  
4 #Regex to validate user name  
5 com.openexchange.authentication.cloudplugins.user.regex= [0-9a-zA-Z.@]*  
6  
7 # Setting to control the start of the own authenticationService which would be used as a  
   fallback in the Tracker if started  
8 # Default: true  
9 com.openexchange.authentication.cloudplugins.enableauthentication=true  
10  
11 # Comma seperated blacklist of hostnames that should not be handled by the default  
   authenticationService  
12 # Default: <empty>  
13 com.openexchange.authentication.cloudplugins.authentication.blacklist=  
14  
15 # Setting to control the start of the CloudAuthenticationDriverTracker  
16 # Default: true  
17 com.openexchange.authentication.cloudplugins.enable.authentication.tracker=true
```

File 3 /opt/open-xchange/etc/cloudplugins-master-auth-servlet.properties

```
1 #  
2 # login name of httpauth user to access the master auth api  
3 #  
4 com.openexchange.cloudplugins.master.auth.httpauth.login=  
5  
6 #  
7 # password of httpauth user  
8 #  
9 com.openexchange.cloudplugins.master.auth.httpauth.password=
```

File 4 /opt/open-xchange/etc/cloudplugins-cassandra.properties

```
1 # turn on/off cassandra integration  
2 # possible values: true/false  
3 com.openexchange.cloudplugins.useCassandra = false  
4  
5 # keyspace to use in cassandra  
6 com.openexchange.cloudplugins.cassandraKeyspace = ox  
7  
8 # comma separated list of brands which logins should be recorded to cassandra  
9 com.openexchange.cloudplugins.cassandra.loginrecorder.remoteipfor.brands=  
10  
11 # comma separated list of brands where alias creation and deletion time should be recorded  
   to cassandra  
12 com.openexchange.cloudplugins.cassandra.loginrecorder.createdeletealias.brands=  
13
```



```
14 # comma separated list of brands where mail autoforward active flag should be set
15 com.openexchange.cloudplugins.cassandra.autoforward.record.brands=
```

File 5 /opt/open-xchange/etc/cloudplugins.properties

```
1
2 # ldap url for read access
3 com.openexchange.cloudplugins.read.ldapurl=ldap://localhost:389
4
5 # admin dn for read access
6 com.openexchange.cloudplugins.read.binddn=cn=oxadmin,o=oxcs
7
8 # admin dn password for read access
9 com.openexchange.cloudplugins.read.bindpassword=
10
11 # ldap url for write access
12 com.openexchange.cloudplugins.write.ldapurl=ldap://localhost:389
13
14 # admin dn for write
15 com.openexchange.cloudplugins.write.binddn=cn=oxadmin,o=oxcs
16
17 # admin dn password for write access
18 com.openexchange.cloudplugins.write.bindpassword=
19
20 # tree for brands
21 com.openexchange.cloudplugins.branddn=ou=brands,o=oxcs
22
23 # tree for other stuff like mailstores
24 com.openexchange.cloudplugins.configdn=ou=config,o=oxcs
25
26 # tree for contexts
27 com.openexchange.cloudplugins.contextdn=ou=contexts,o=oxcs
28
29 # password for doveadm service
30 com.openexchange.cloudplugins.doveadmPassword=
31
32 # This timeout only works since Java 6 SE to time out waiting for a response.
33 com.openexchange.cloudplugins.read.timeout=10000
34
35 # Specifies the connect timeout (in milliseconds) when establishing a connection to the
    LDAP end-point
36 #
37 # Default is 5000 (5 seconds)
38 com.openexchange.cloudplugins.connect.timeout=5000
39
40 # Algorithm to use to encrypt passwords
41 # valid values are: SSHA and SSHA-384
42 com.openexchange.cloudplugins.password.algorithm=SSHA
43
44 # how long should the random salts be
45 com.openexchange.cloudplugins.password.algorithm.saltlength=64
46
47 # HTTP Header from which the brand name is fetched
48 com.openexchange.cloudplugins.header=host
49
50 # can a user change the password without providing the old one?
51 # default is false
52 com.openexchange.capability.password_change_without_old_password=false
53
54 # use ldapbind as password verification (true) or retrieve password digest from
55 # ldap using provided read credentials and do the check locally (false)
56 # NOTE: local password check only works when setting
57 # com.openexchange.cloudplugins.password.algorithm to SSHA or SSHA384
58 # and all existing users must have the userPassword encoded with any of those mechanisms.
59 com.openexchange.cloudplugins.passwordcheck.ldapbind=true
60
61 # Comma separated list of brands that where aliases should be moved into deleted tree
62 com.openexchange.cloudplugins.store.deleted.alias.brands=
```

```

63
64 # jndi ldap pool configuration
65 # see http://docs.oracle.com/javase/jndi/tutorial/ldap/connect/config.html for more
   information
66 com.openexchange.cloudplugins.pool=true
67 com.openexchange.cloudplugins.pool.initsize=1
68 com.openexchange.cloudplugins.pool.maxsize=20
69 com.openexchange.cloudplugins.pool.prefsiz=10
70 com.openexchange.cloudplugins.pool.timeout=300000
71 com.openexchange.cloudplugins.pool.protocol=plain
72
73 # Allowed encryption methods for LDAP userPassword
74 # internal default: MD5,SHA,CRYPT,SSHA,SSHA384
75 com.openexchange.cloudplugins.setPasswordHash.allowedMethods=MD5,SHA,CRYPT,SSHA,SSHA384

```

File 6 /opt/open-xchange/etc/doveadm-config.properties

```

1 # Api secret
2 com.openexchange.cloudplugins.dovecot.apiSecret=
3
4 # Dovecot port
5 com.openexchange.cloudplugins.dovecot.port=8080
6
7 # Protocol to use
8 com.openexchange.cloudplugins.dovecot.protocol=http://
9
10 # Dovecot host
11 com.openexchange.cloudplugins.dovecot.host=localhost
12
13 # Path to dovecot commands
14 com.openexchange.cloudplugins.dovecot.path=/doveadm/v1
15
16 # How many contexts per request should be transmitted
17 com.openexchange.cloudplugins.dovecot.contextChunks=100
18
19 # Max number of http connections
20 com.openexchange.cloudplugins.dovecot.maxConnections=100
21
22 # Max number of http connections per host
23 com.openexchange.cloudplugins.dovecot.maxConnectionsPerHost=100
24
25 # The connection timeout in milliseconds
26 com.openexchange.cloudplugins.dovecot.connectionTimeout=5000
27
28 # The socket read timeout in milliseconds
29 com.openexchange.cloudplugins.dovecot.socketReadTimeout=15000

```

File 7 /opt/open-xchange/etc/nginx-auth-servlet.properties

```

1 # Regex to validate brandName value
2 com.openexchange.cloudplugins.nginx.auth.servlet.brandName.regex= [0-9a-zA-Z.]*
3
4 # Regex to validate user name
5 com.openexchange.cloudplugins.nginx.auth.servlet.uid.regex= [0-9a-zA-Z.@]*
6
7 # Configure the LDAP lookup method to find users using their logins.
8 # It is the method that is used by default when there is no brand specific
9 # configuration setting).
10 #
11 # Optional, defaults to "uid".
12 #
13 # Possible values:
14 # uid

```

```

15 # attempts to find users by matching their login against the uid attribute.
16 # email
17 # attempts to find users by matching their login against the alias attribute.
18 # auto
19 # when the login contains a "@", the "email" method is used and when not,
20 # the "uid" method is used
21 # uid-or-email
22 # attempts to find users by matching their login against the uid and the alias
23 # attributes (either may match)
24 #
25 # Note that this only applies to the default authentication driver. If there
26 # is a custom implementation that is used for a given brand, its behavior is
27 # not influenced by this properties.
28 #
29 # Example:
30 # com.openexchange.cloudplugins.nginx.auth.servlet.uid.mode=auto
31
32 # One may define any number of such settings per brand by setting properties
33 # with the following format for their name:
34 #
35 # com.openexchange.cloudplugins.nginx.auth.servlet.uid.mode.<brand>=<uid|email|auto|uid-or-
    -email>
36 #
37 # For the list of possible values, please consult the documentation for
38 # com.openexchange.cloudplugins.nginx.auth.servlet.uid.mode
39 #
40 # Optional, defaults to falling back to the method configured in
41 # com.openexchange.cloudplugins.nginx.auth.servlet.uid.mode
42 #
43 # Note that this only applies to the default authentication driver. If there
44 # is a custom implementation that is used for a given brand, its behavior is
45 # not influenced by these properties.
46 #
47 # Example:
48 #
49 # com.openexchange.cloudplugins.nginx.auth.servlet.uid.mode.brand1=auto
50 # com.openexchange.cloudplugins.nginx.auth.servlet.uid.mode.brand2=uid

```

File 8 /opt/open-xchange/etc/cloudquotaservice.properties

```

1 # Identifier of the default quota driver to use when not
2 # superseded by a per-brand configuration setting (see below).
3 #
4 # This configuration property is optional.
5 # When it is not set, it will attempt to use the "dovecot"
6 # driver, if available (installed).
7 # If the "dovecot" driver is not installed, it will use the
8 # highest ranked driver that is installed.
9 #
10 # For a deterministic approach, it is recommended to set
11 # a value for this configuration setting.
12 #
13 # Example:
14 # com.openexchange.cloudplugins.quota.default.driver=cassandra
15 com.openexchange.cloudplugins.quota.default.driver=
16
17 # Override the quota driver per brand.
18 #
19 # Use property names that start with
20 # "com.openexchange.cloudplugins.quota.driver."
21 # followed by the brand name (not the complete DN
22 # but just the brand name).
23 #
24 # These are optional and, if not defined, will always fall
25 # back to the driver configured in the property
26 # com.openexchange.cloudplugins.quota.default.driver
27 #
28 # Example:

```

```

29 # com.openexchange.cloudplugins.quota.driver.brand1=cassandra
30 # com.openexchange.cloudplugins.quota.driver.otherbrand=cassandra
31 #

```

File 9 /opt/open-xchange/etc/cloudquotaservice-cassandra.properties

```

1 # Use the legacy "type" value for lookups in the Cassandra
2 # quota table.
3 # In recent deployments, the "type" parameter is "dovecot_mail",
4 # but in previous installments, the "type" used to be null.
5 # Setting this property to true will use null for the "type"
6 # query parameter.
7 #
8 # This property is optional and when not set, defaults to false.
9 #
10 # Example:
11 # com.openexchange.cloudplugins.quota.use.legacy.type=true
12 #
13 com.openexchange.cloudplugins.quota.use.legacy.type=false
14
15 # Unified quota performance optimizations.
16 #
17 # The default behavior is to check whether every single user
18 # who's usage quota is retrieved has unified quota enabled or not,
19 # and return data accordingly.
20 #
21 # In most use cases, if not all, unified quota will be enabled or
22 # disabled uniformly
23 # - globally for a platform,
24 # - or globally for a brand,
25 # - or for a whole context,
26 # in which case the implementation can avoid or minimize the amount
27 # of queries it needs to perform in order to determine how to
28 # calculate the quota usage, depending on whether unified quota
29 # is enabled or disabled for a user.
30 #
31 # Two configuration settings govern this behavior:
32 # - the default behavior which is used for every brand on a platform
33 #   (com.openexchange.cloudplugins.quota.unified.quota)
34 # - per-brand behaviors which take precedence over the default
35 #   (com.openexchange.cloudplugins.quota.unified.quota.<brand name>)
36 #
37 # Each of those settings can have one of the following values:
38 #
39 # always
40 #   the implementation will assume that unified quota is enabled for
41 #   all contexts within the brand, or for all contexts within all
42 #   brands if applied to the default setting
43 #
44 # never
45 #   the implementation will assume that unified quota is disabled for
46 #   all contexts within the brand, or for all contexts within all
47 #   brands if applied to the default setting
48 #
49 # context
50 #   the implementation will only check whether unified quota has
51 #   been enabled for the context the user(s) are in, and not for
52 #   each individual user, assuming that all users within the same
53 #   context are always configured uniformly regarding unified quota,
54 #   be it enabled or disabled
55 #
56 # user
57 #   the implementation will make no assumptions and check whether
58 #   unified quota is enabled or not for every individual user -- this
59 #   is the safest setting, which is why it is the default, but also
60 #   the slowest and should be avoided if possible
61 #
62 #

```

```

63 # The default setting can be configured using the property
64 # com.openexchange.cloudplugins.quota.unified.quota=...
65 #
66 # It is optional and defaults to "user" (as explained above) if
67 # omitted, commented out or left empty.
68 #
69 # Example:
70 # com.openexchange.cloudplugins.quota.unified.quota=never
71 com.openexchange.cloudplugins.quota.unified.quota=
72
73 # Per-brand settings can be configured using the following
74 # prefix, followed by the name of the brand:
75 # com.openexchange.cloudplugins.quota.unified.quota.<brand name>=...
76 #
77 # Example:
78 # com.openexchange.cloudplugins.quota.unified.quota.my_brand=always
79 # com.openexchange.cloudplugins.quota.unified.quota.my_other_brand=context
80 #
81 # Those are obviously optional and default to using the default
82 # setting above (which, in turn, when omitted, defaults to "user").
83 #

```

File 10 /opt/open-xchange/etc/cloudplugins_report.properties

```

1 # Where the report and its parts should be stored
2 com.openexchange.cloudplugins.report.storagePath=/tmp
3
4 # How many contexts can be stored in memory before writing them on hdd
5 com.openexchange.cloudplugins.report.maxChunkSize=200
6
7 # How many parallel threads can work on the report
8 com.openexchange.cloudplugins.report.maxThreadPoolSize=20
9
10 # Report thread priority
11 com.openexchange.cloudplugins.report.threadPriority=1
12
13 # Max number of entities that will be included in an ldap search
14 com.openexchange.cloudplugins.report.maxLdapChunks=20000

```

File 11 /opt/open-xchange/etc/cloudplugins-blackwhitelist-ldap.properties

```

1 # Identifier of this blackwhitelist connector: cloudplugins_blackwhitelist_ldap
2 # ldap uri
3 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.uri=remote.url.for.ldap
4
5 # ldap port
6 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.port=389
7
8 # ldap user
9 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.user=cn=oxadmin,o=oxcs
10
11 # ldap password
12 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.passwd=
13
14 # ldap base, can be empty
15 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.base=ou=lists,o=oxcs
16
17 # ldap search filter
18 # possible template values {{usercontext}}
19 # usercontext is build as 'userid + "@" + contextid'
20 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.searchFilter=
    oxLocalMailrecipient={{usercontext}}
21

```

```

22 # ldap DN to create when an entry is missing
23 # possible template values {{usercontext}}, {{brand}}
24 # usercontext is build as 'userid + "@" + contextid'
25 # brand is searched from default LDAP
26 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.user.dn=oxLocalMailrecipient
    ={{usercontext}},bn={{brand}},ou=lists,o=oxcs
27
28 # ldap maximum pool size
29 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.pool.size=10
30
31 # ldap max requests before connection is closed
32 # can be set to -1 to be disabled
33 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.pool.max.requests=2000
34
35 # ldap max lifetime in seconds for each connection in the pool
36 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.pool.max.lifetime=120
37
38 # config to enable LDAP SSL connection over ldaps
39 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.useSSL=false
40
41 # Setting to check if memory backed test mock should be started
42 # This connector is identified by cloudplugins_blwl_test
43 # Default: false
44 com.openexchange.cloudplugins.blackwhitelist.connector.ldap.test=false

```

File 12 /opt/open-xchange/etc/mailfilter-interceptor-drivers.properties

```

1 # This is the CloudPlugins MailFilterInterceptorDriver configuration
2 #
3 # Enable drivers by adding at least one brand in the brands property for that driver
4 # on the server level configuration. If no brand exists, the driver will not be registered
5 #
6 # Some drivers may also have additional configurations
7
8
9 ##### Driver Brand Lists #####
10 # Comma delimited lists
11
12 # Brands that the RedirectStatusDriver should be enabled for
13 #
14 # Optional - default is no brands
15 com.openexchange.cloudplugins.mailfilter.intercept.drivers.redirect.status.driver.brands=
16
17 # Brands that the RedirectBlacklistDriver should be enabled for
18 #
19 # Optional - default is no brands
20 com.openexchange.cloudplugins.mailfilter.intercept.drivers.redirect.blacklist.driver.
    brands=
21
22 ##### End Driver Brand Lists #####
23
24
25
26 ##### Driver Specific configurations #####
27
28 ### Redirect Blacklist Driver ###
29 #
30 # Set to true to enable config cascade for all properties of the Redirect Blacklist Driver
31 #
32 # This should be used to set different configurations per brand or an even lower level.
33 # This property is NOT config cascade aware as it is used to control use of it.
34 # Even the driver brand list property can be config cascade if this is enabled which would
35 # be useful
36 # to enable it for a brand, but disable it for some users
37 #
38 # Optional - default is false
39 com.openexchange.cloudplugins.mailfilter.intercept.drivers.redirect.blacklist.driver.
    configcascade.enable=false

```

```

38 #
39 # The comma+space delimited list of regular expressions that are blacklisted for mail
    filter redirects.
40 # Java regular expressions are supported here, so non regex characters must be escaped.
41 # Example: abuse@.*, spam@domain\.com <-- '.' has been escaped to match only '.' and not
    any char
42 # See for regex constructs: https://docs.oracle.com/javase/7/docs/api/java/util/regex/
    Pattern.html
43 # WARNING: You must use ", " (comma and a space) as the separator to separate the regexs
44 #
45 # Optional - default is empty which should only be left if this driver is not used
46 com.openexchange.cloudplugins.mailfilter.intercept.drivers.redirect.blacklist.driver.
    blacklist=
47 #
48 # Set to true to only blacklist true autoforward rules which are defined by having the "
    autoforward" flag.
49 # If set to false, then all redirect rules will be checked for the blacklist addresses
50 #
51 # Optional - default is true
52 com.openexchange.cloudplugins.mailfilter.intercept.drivers.redirect.blacklist.driver.
    autoforward.only=true
53 #
54 ### End Redirect Blacklist Driver ###
55
56 ##### End Driver Specific configurations #####

```

File 13 /opt/open-xchange/etc/cloudplugins-saml.properties

```

1 # The properties for cloud setup SAML bundle
2
3 ### General settings
4 #####
5
6 # This setting is used to disable other authentication strategies and will internally
    register a DisabledAuthenticationService
7 # Default: false
8 com.openexchange.cloudplugins.saml.disableOtherAuthentication=false
9
10 # The id inside the saml response which holds the userinformation
11 com.openexchange.cloudplugins.saml.id="default_id"
12
13 # URL of where the users are redirected after logout
14 com.openexchange.cloudplugins.saml.logout.redirect.url="https://www.google.com"
15
16 # Regex to validate host HTTP Header value
17 com.openexchange.cloudplugins.saml.host.regex=[0-9a-zA-Z.]*
18
19 # Regex to validate user name
20 com.openexchange.cloudplugins.saml.user.regex=[0-9a-zA-Z.@]*
21
22 # The domain to use for OXaaS LDAP authentication operations.
23 # Uses the host name when empty or not set.
24 com.openexchange.cloudplugins.saml.domain=
25
26 # The URL to redirect to in case the SAML back-end fails to look up the authenticated user
    .
27
28 # When left empty or not set, an HTTP 500 error page is sent instead.
29 com.openexchange.cloudplugins.saml.failure.redirect=
30
31
32 ### Key-store/certificate settings
33 #####
34
35 # The full path to a Java keystore containing the IdPs certificate.
36 #
37 # Default: <empty>
38 com.openexchange.cloudplugins.saml.keyStore=

```

```

39
40 # Password to open the keystore.
41 #
42 # Default: <empty>
43 com.openexchange.cloudplugins.saml.keyStorePass=
44
45 # The alias of the IdP certificate entry within the above specified
46 # keystore.
47 #
48 # Default: <empty>
49 com.openexchange.cloudplugins.saml.certAlias=
50
51 # The alias of the signingKey entry within the above specified
52 # keystore.
53 #
54 # Default: <empty>
55 com.openexchange.cloudplugins.saml.signingKeyAlias=
56
57 # The password of the signingKey entry within the above specified
58 # keystore.
59 #
60 # Default: <empty>
61 com.openexchange.cloudplugins.saml.signingKeyPassword=
62
63 # The alias of the decryptionKey entry within the above specified
64 # keystore.
65 #
66 # Default: <empty>
67 com.openexchange.cloudplugins.saml.decryptionKeyAlias=
68
69 # The password of the decryptionKey entry within the above specified
70 # keystore.
71 #
72 # Default: <empty>
73 com.openexchange.cloudplugins.saml.decryptionKeyPassword=

```

File 14 /opt/open-xchange/etc/settings/externalcontent.properties

```

1 io.ox.externalcontent//widget/widgetName=External Content
2 io.ox.externalcontent//widget/widgetName_en_GB=
3 io.ox.externalcontent//widget/widgetName_de_DE=

```

File 15 /opt/open-xchange/etc/oxaas-alias.properties

```

1 # Setting to control the uri of the tarent adapter
2 com.openexchange.oxaas.alias.tarent.uri=http://localhost
3
4 # Setting to control allowed domains
5 com.openexchange.oxaas.alias.allowed.domains=
6
7 # Setting to control if alias adapter should be in test mode (this means a mock is used)
8 com.openexchange.oxaas.alias.test=false
9
10 # Loglevel for the internal OkHttp3 client
11 # Allowed values are: NONE, BASIC, HEADERS, BODY
12 com.openexchange.oxaas.alias.tarent.loglevel=NONE
13
14 # Setting to control if Unsecured Https should be allowed or not
15 # Default: false
16 com.openexchange.oxaas.alias.tarent.allowUnsecuredHttps=false
17
18 # Master user needed to delete alias
19 com.openexchange.oxaas.alias.master.user=

```



```

20
21 # Master user password needed to delete alias
22 com.openexchange.oxaas.alias.master.password=
23
24 # Setting to control if a client cert should be loaded, must be in PKCS 12 format
25 # Can be mixed with com.openexchange.oxaas.alias.tarent.allowUnsecuredHttps
26 # allowUnsecuredHttps=true and clientcert.path=set
27 # a client cert is used but the hostname is not verified and all server certs are
  trusted
28 # allowUnsecuredHttps=false and clientcert.path=set
29 # a client cert is used, but hostname is verified and server certs must be trustable
30 # Default: empty
31 com.openexchange.oxaas.alias.tarent.ssl.clientcert.path=
32
33 # Setting that holds the password for the PKCS 12 container
34 # Default: empty
35 com.openexchange.oxaas.alias.tarent.ssl.clientcert.password=

```

File 16 /opt/open-xchange/etc/oxaas-mail-notification-templates.properties

```

1 # Config cascade-aware property to control the prefix of the users templates
2 # For each prefix and each user configured percentage
3 com.openexchange.oxaas.mail.quota.notify.prefix=notify.oxaas.over.quota
4
5 # Config cascade-aware property to control the prefix of the users templates
6 # For each prefix and each user configured percentage
7 com.openexchange.oxaas.mail.welcome.mail.notify.prefix=notify.oxaas.welcome.mail
8
9 # Config cascade-aware property to control the prefix of the users templates
10 # For each prefix and each user configured percentage
11 com.openexchange.oxaas.mail.removed.sent.spam.notify.prefix=notify.oxaas.disable.sent.spam

```

File 17 /opt/open-xchange/etc/oxaas-drive-quota-notification.properties

```

1 # Config-cascade aware setting to control the quotas that should be monitored
2 com.openexchange.oxaas.mail.quota.drive.quotas=90,100
3
4 # Config-cascade aware setting to control if the admin should also receive a mail, in case
  the filestore is context-wide
5 com.openexchange.oxaas.mail.quota.drive.updateAdmin=false
6
7 # Config-cascade aware setting to control how often a mail should be sent
8 # Default is 86400 (1 day)
9 # Set to 0 to ignore that and always send a new mail
10 com.openexchange.oxaas.mail.quota.drive.mail.seconds=86400

```

File 18 /opt/open-xchange/etc/oxaas-mail-unread.properties

```

1 # Value holding the usernames for basic authentication
2 # must be the username for basic auth split by ,
3 # e.g hosterone,hostertwo
4 com.openexchange.oxaas.mail.unread.ws.basic.usernames=
5
6 # Setting to control basic auth username
7 # example would be com.openexchange.oxaas.mail.unread.ws.basic.hosterone.brand=
  internalBrandForhosterone
8 #com.openexchange.oxaas.mail.unread.ws.basic.[username].brand=
9
10 # Setting to control basic auth password

```

```
11 # example would be com.openexchange.oxaas.mail.unread.ws.basic.hosterone.password=  
    verySecretPassword  
12 #com.openexchange.oxaas.mail.unread.ws.basic.[username].password=
```

File 19 /opt/open-xchange/etc/oxaas-mail.properties

```
1 # Value holding the usernames for basic authentication  
2 # must be the username for basic auth split by ,  
3 # e.g hosterone,hostertwo  
4 com.openexchange.oxaas.mail.ws.basic.usernames=  
5  
6 # Setting to optimize the fetching of recentMessages  
7 # If set to true, the virtual/all folder will be queried  
8 # If set to false, the calculation is done in the middleware  
9 # config-cascade aware  
10 com.openexchange.oxaas.mail.ws.recentMessagesFromVirtualAll=false  
11  
12 # Setting to control basic auth username  
13 # example would be com.openexchange.oxaas.mail.basic.hosterone.password=verySecretPassword  
14 #com.openexchange.oxaas.mail.ws.basic.[username].password=  
15  
16 # Setting to control basic auth password  
17 # example would be com.openexchange.oxaas.mail.basic.hosterone.brand=  
    internalBrandForhosterone  
18 #com.openexchange.oxaas.mail.ws.basic.[username].brand=
```