



**OX App Suite Univention Plugins Release Notes for  
7.10.4**

2020-12-14

## Copyright notice

---

©2020 by OX Software GmbH. All rights reserved. Open-Xchange and the Open-Xchange logo are trademarks or registered trademarks of OX Software GmbH. All other company and/or product names may be trademarks or registered trademarks of their owners. Information contained in this document is subject to change without notice.

## Contents

<b>1</b>	<b>General Information</b>	<b>2</b>
1.1	Warnings	2
1.2	Delivery Comment	2
1.3	Install Package Repository	2
1.4	Build Dependencies	2
1.5	Notice	2
<b>2</b>	<b>Univention OpenID Connect handler</b>	<b>2</b>
2.1	Configuration	3
<b>3</b>	<b>Shipped Packages and Version</b>	<b>3</b>
3.1	Package open-xchange-authentication-ucs	3
3.1.1	Installation	3
3.2	Package open-xchange-authentication-ucs-common	4
3.2.1	Installation	4
3.2.2	Configuration	4
3.3	Package open-xchange-oidc-ucs	4
3.3.1	Installation	4
3.4	Package open-xchange-saml-ucs	4
3.4.1	Installation	5
<b>4</b>	<b>Changes relevant for Operators</b>	<b>5</b>
4.1	Changes of Behavior	5
<b>5</b>	<b>Tests</b>	<b>5</b>
<b>A</b>	<b>Configuration Files</b>	<b>5</b>

## 1 General Information

### 1.1 Warnings

 **Warning**

This preview delivery is not for productive usage and not affected by service-level agreements.

 **Warning**

It is mandatory to restart the **open-xchange** service on all middleware nodes after performing the update.

 **Warning**

Custom configuration or template files are potentially not updated automatically. After the update, please always check for files with a **.dpkg-new** or **.rpmnew** suffix and merge the changes manually. Configuration file changes are listed in their own respective section below but don't include changes to template files. For details about all the configuration files and templates shipped as part of this delivery, please read the relevant section of each package.

### 1.2 Delivery Comment

This delivery was requested with following comment:

*Univention 7.10.4 Feature Delivery for OIDC - add userinfo lookup*

### 1.3 Install Package Repository

This delivery is part of a restricted preview software repository:

<https://software.open-xchange.com/components/univention/preview/7.10.4/DebianBuster>  
<https://software.open-xchange.com/components/univention/preview/7.10.4/DebianStretch>  
<https://software.open-xchange.com/components/univention/preview/7.10.4/RHEL7>

### 1.4 Build Dependencies

This delivery was build with following dependencies:

AppSuite:node-10,frontend-7.10.4-rev14,backend-7.10.4-rev14

### 1.5 Notice

 **Info**

Some configurations can be changed without restarting the service, please call following command for getting a list of supported settings.

`/opt/open-xchange/sbin/listreloadables`

Please use following command to enable capable and changed configurations on a running system.

`/opt/open-xchange/sbin/reloadconfiguration`

## 2 Univention OpenID Connect handler

Story for original implementation:

[UNI-14](#) & [UNI-41](#)

Code repository:	<a href="https://gitlab.open-xchange.com/extensions/univention">https://gitlab.open-xchange.com/extensions/univention</a>
Package(s):	open-xchange-oidc-ucs
Required capabilities:	none, please see <b>Configuration</b> section for further information
Available since:	7.10.4
Maintainers:	Felix Marx

The OpenID Connect handler for Univention uses the default ldap backend to to the user lookups. In addition the connector is able to perform a userinfo lookup instead of relying on the IdToken.

## 2.1 Configuration

The OpenID Connect handler uses the core framework which is also explained on [documentation.open-xchange.com - middleware - OpenID](https://documentation.open-xchange.com - middleware - OpenID) in detail.

Available config options are also explained on [documentation.open-xchange.com - middleware configuration - OpenID](https://documentation.open-xchange.com - middleware configuration - OpenID).

In addition to the default config options, the following additional options are available:

Property	Default Value	Option
com.openexchange.oidc.ucs.enabled	false	enables the oidc backend for univention
com.openexchange.oidc.ucs.userInfoEndpoint	""	if configured, uses the userInfoEndpoint instead of relying on the IdToken claims

When the com.openexchange.oidc.ucs.userInfoEndpoint is configured, the [userLookupClaim](#) will search inside the response from the userInfoEndpoint instead of the IdToken.

## 3 Shipped Packages and Version

### 3.1 Package open-xchange-authentication-ucs

Module for authenticating users on a Univention Corporate Server installation This package installs the OSGi bundle implementing the OSGi AuthenticationService for the backend. The implementation uses Univention Corporate Server to authenticate login requests. This authentication module is mutually exclusive with any other authentication module. Only one authentication module can be installed on the backend.

Version: 7.10.4-2

Type: OX Middleware Plugin

Depends on:

```
open-xchange-authentication-ucs-common (<<7.10.5)
open-xchange-authentication-ucs-common (>=7.10.4)
open-xchange-core (<<7.10.5)
open-xchange-core (>=7.10.4)
```

Conflicts with:

```
open-xchange-authentication-database
open-xchange-authentication-ldap
open-xchange-authentication-ldap
```

#### 3.1.1 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-authentication-ucs
```

### 3.2 Package open-xchange-authentication-ucs-common

Common Module for authenticating users on a Univention Corporate Server installation This package installs the OSGi bundle implementing the common helper service that uses Univention Corporate Server to authenticate login requests.

Version: 7.10.4-2

Type: OX Middleware Plugin

Depends on:

```
open-xchange-core (<<7.10.5)
open-xchange-core (>=7.10.4)
```

#### 3.2.1 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-authentication-ucs-common
```

#### 3.2.2 Configuration

For details, please see appendix [A](#)  
/opt/open-xchange/etc/authplugin.properties (page [6](#))

### 3.3 Package open-xchange-oidc-ucs

Module for authenticating users on a Univention Corporate Server installation via OIDC This package installs the OSGi bundle implementing the OSGi OIDCBackend for the backend. The implementation uses Univention Corporate Server to authenticate login requests.

Version: 7.10.4-2

Type: OX Middleware Plugin

Depends on:

```
open-xchange-authentication-ucs-common (<<7.10.5)
open-xchange-authentication-ucs-common (>=7.10.4)
open-xchange-core (<<7.10.5)
open-xchange-core (>=7.10.4)
open-xchange-oidc (<<7.10.5)
open-xchange-oidc (>=7.10.4)
```

#### 3.3.1 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-oidc-ucs
```

### 3.4 Package open-xchange-saml-ucs

Module for authenticating users on a Univention Corporate Server installation via SAML This package installs the OSGi bundle implementing the OSGi SAMLBackend for the backend. The implementation uses Univention Corporate Server to authenticate login requests.

Version: 7.10.4-2

Type: OX Middleware Plugin

Depends on:

```
open-xchange-authentication-ucs-common (<<7.10.5)
open-xchange-authentication-ucs-common (>=7.10.4)
```

```
open-xchange-core (<<7.10.5)
open-xchange-core (>=7.10.4)
open-xchange-saml-core (<<7.10.5)
open-xchange-saml-core (>=7.10.4)
```

### 3.4.1 Installation

Install on OX middleware nodes with package installer **apt-get** or **yum**:

```
<package installer> install open-xchange-saml-ucs
```

## 4 Changes relevant for Operators

### 4.1 Changes of Behavior

#### UNI-41 Univention OIDC: add userinfo lookup

Status: Done

Resolution: Done

Affected Packages: open-xchange-oidc-ucs

## 5 Tests

As this is a preview delivery, no QA tests have been performed.

## A Configuration Files

### File 1 /opt/open-xchange/etc/authplugin.properties

```

1  # use ldap pooling
2  com.openexchange.authentication.ucs.useLdapPool=false
3
4  # basedn of ldap directory
5  com.openexchange.authentication.ucs.baseDn=dc=example,dc=org
6
7  # ldap url; use ldaps:// for ssl
8  com.openexchange.authentication.ucs.ldapUrl=ldap://localhost
9
10 # specify attribute containing email address from which domain part will be used to
11 # identify context
12 com.openexchange.authentication.ucs.mailAttribute=mailPrimaryAddress
13
14 # ldap attribute containing the OX Login name
15 com.openexchange.authentication.ucs.loginAttribute=uid
16
17 # specify name of attribute containing contextId in order to lookup context
18 # this is optional; if not specified, context lookup will be done using domain name as
19 # found
20 com.openexchange.authentication.ucs.mailAttribute
21 com.openexchange.authentication.ucs.contextIdAttribute=
22
23 # search query to find the user within ldap
24 # %s will be replaced by the login as entered in the ox login mask
25 com.openexchange.authentication.ucs.searchFilter=(&(objectClass=oxUserObject)(|(uid=%s)(
26 mailPrimaryAddress=%s)))
27
28 # where to redirect users that need to change their password when it is expired
29 com.openexchange.authentication.ucs.passwordChangeURL=

```

```
    access
30 com.openexchange.authentication.ucs.bindDn=
31
32 # password for specified binddn
33 com.openexchange.authentication.ucs.bindPassword=
```